

Safety Data Sheet

Product Number: 51-0006-01 Date: 7/18/2019
Product Name: Ink, Acetone White Opaque Revision: B

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2015/830

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name: **Ink, Acetone White Opaque**
Product Code: **51-0006-01**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product Use: Printing ink for use in BestCode CIJ

1.3 Details of the supplier of the safety data sheet

BestCode
3034 SE Loop 820
Fort Worth, TX 76140
817-349-8555

For further information, please contact Customer Service:

Customer Service: 817-349-8555
Email: Info@Bestcode.co

1.4 Emergency telephone number

Emergency Contact: Local Poison Information Center
Chem Tel. Inc. Toll Free 800-255-3924
International 813-248-0585

Section 2: Hazards identification

2.1 Classification of the mixture in accordance with Article 40 of Regulation (EC) No 1272/2008

GHS Rating:

Flammable liquid - Category 2
Eye Corrosive - Category 2A
Specific Target Organ Toxicity, Single Exposure - Category 3

2.2 Label elements



Signal word: **Danger**



Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

Hazard statements:

H225 Highly flammable liquid and vapor
H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash hands thoroughly after handling
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection/face protection.
P312 Call a poison center/doctor if you feel unwell.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 Get medical advice/attention
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container to industrial combustion plant.

2.3 Other Hazards

N/A

Safety Data Sheet

Product Number: 51-0006-01 Date: 7/18/2019
 Product Name: Ink, Acetone White Opaque Revision: B

Section 3: Composition/information on ingredients

3.1 Substances:

3.2 Mixtures:

CAS #	EC #	Hazardous components / REACH Registration No.	Concentration	GHS Classification
67-64-1	200-662-2 606-001-00-8	Acetone	60.0-60.0%	Flam. Liq. 2: H225 Eye Damage 2: H319 STOT (SE) 3: H336 EUH066
13463-67-7	236-675-5	Titanium Dioxide	20.0%-30.0%	
123-86-4	607-025-00-1	N-Butyl Acetate	5.0%-10.0%	TOST (SE) 3: H336

Section 4: First Aid Measures

4.1 Description of first aid measures

Inhalation: Move exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep affected person warm and at rest. Seek medical attention.

Eyes: Promptly wash eyes with plenty of water while lifting the eyelids. Remove contact lenses, if worn. Continue to rinse for at least 15 minutes. Seek medical attention, preferably with an ophthalmologist.

Skin: Remove contaminated clothing. Wash affected area with plenty of soap and water. Seek medical attention if irritation develops or persists.

Ingestion: NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If affected person is conscious and alert, give 2 to 3 glasses of water to dilute the swallowed material. Do not induce vomiting. If vomiting occurs, the head should be kept low so the stomach vomit does not enter the lungs. Seek medical attention.

4.2 Most Important symptoms and effects, both acute and delayed

None under normal use.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to doctor:

Propanone is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs may be aggravated by exposure to this material: skin, lungs (for example, asthma-like conditions).

Section 5: Fire Fighting Measures

5.1 Extinguishing media

Use: foam, dry chemical, water spray.

5.2 Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards: Material can accumulate static charge, which can cause an incendiary electrical discharge. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Hazardous Combustion Products: Fire creates toxic gases/vapors/fumes or carbon monoxide (CO), carbon dioxide (CO₂) and/or nitrous oxides.

5.3 Advice for firefighters

Special Procedures: Keep run-off water out of sewer and water sources. Dike for water control. If risk of water pollution occurs, notify appropriate authorities. Use water to keep fire exposed containers cool and disperse vapors. Move container from the fire area if it can be done without risk. Do not direct a solid stream of water or foam into hot, burning pools; this may cause frothing and increase fire intensity.

Personal Protective Equipment: Wear approved/certified self-contained breathing apparatus and full protective gear.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Remove persons to safety.

6.1.2 For emergency responders

Chemical splash goggles, protective clothing, gloves. Use approved respirator if air contamination is above accepted risk level.

6.2 Environmental Precautions

K Do not allow material to enter into public sewer system, waterway, or ground. If large amounts of material are released, report to appropriate local and/or state agencies.



Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

6.3 Methods and material for containment and cleaning up

6.3.1 For Containment:

Ventilation. Stop leak if it can be done without risk. If needed, dike spill using absorbent or impervious material such as vermiculite, dry sand, clay, or earth.

6.3.2 Clean up and disposal of spill:

Collect spills with absorbent, non-combustible material into suitable containers.

Section 7: Handling and storage

7.1 Precautions for safe handling

Handling Precautions: Keep away from heat, sparks, and open flame. Avoid spilling, skin and eye contact. Use in well ventilated area, avoid breathing vapors. Protect material from direct sunlight. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures. Do not pressurize, cut, heat or weld containers. Empty containers may contain product residue. Do not reuse empty containers.

7.2 Conditions for safe storage, including any compatibilities

Storage Precautions: Keep container closed to prevent contamination. Store at an ambient temperature. Store in a cool, well ventilated place away from incompatible materials. Do not handle or store near an open flame, heat or other sources of ignition.

7.3 Specific end use(s)

Fluid delivery to BestCode Series 8 CIJ. Follow safety instructions outlined in 7.1 & 7.2 while handling. Observe warnings provided with BestCode Series 8 CIJ system when installing and handling fluids

Section 8: Exposure control/personal protection

8.1 Control parameters

CAS #	Hazardous components	ACGIH TLV	Australia	Austria
67-64-1	Acetone	TLV: 500 ppm STEL: 750 ppm	TWA: 1200 mg/m ³ (500 ppm) STEL: 4800 mg/m ³ (2000 ppm)	TWA: 1185 mg/m ³ (500 ppm) STEL: 2375 mg/m ³ (1000 ppm)
13463-67-7	Titanium Dioxide			STELs - (MAK-KZWs) 10 mg/m ³ STEL [KZW] (alveolar dust, respirable fraction, 2 X 60 min)

Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

				TWAs - (MAK-TMWs) 5 mg/m3 TWA [TMW] (alveolar dust, respirable fraction)
123-86-4	N-Butyl Acetate	150ppm		STELs - (MAK-KZWs) 100 ppm TWAs - (MAK-TMWs) 100 ppm

CAS #	Hazardous components	Belgium OEL	California, USA PELs	Ontario, CA
67-64-1	Acetone	TWA: 1210 mg/m3 (500 ppm) STEL: 2420 mg/m3 (1000 ppm)	TWA: 1200 mg/m3 (500 ppm) STEL: 1780 mg/m3 (750 ppm) CEIL: 3000 ppm	TWA: 500 ppm STEL: 750 ppm
13463-67-7	Titanium Dioxide	10 mg/m3 TWA	5 mg/m3 PEL	10 mg/m3 TWA
123-86-4	N-Butyl Acetate	STELs 200 ppm TWAs 150 ppm		STELs 200 ppm TWAs 150 ppm

CAS #	Hazardous components	China	Québec, CA	German AGS
67-64-1	Acetone		10 mg/m3 TWAEV	
13463-67-7	Titanium Dioxide			
123-86-4	N-Butyl Acetate		STEVs 200 ppm TWAs 150 ppm	TRGS 900 - TWAs (AGWs) 62 ppm

CAS #	Hazardous components	Germany MAK/TRK	Denmark OEL	Spain OEL
67-64-1	Acetone	TWA: 1200 mg/m3 (500 ppm) STEL: 4800 m3/m3 (15min) (4x) (2000 ppm (15min)(4x))	TWA: 600 mg/m3 (250 ppm) STEL: 1200 mg/m3 (500 ppm)	TWA: 1210 mg/m3 (500 ppm)
13463-67-7	Titanium Dioxide		6 mg/m3 TWA	
123-86-4	N-Butyl Acetate	TWAs (MAKs) 100 ppm	TWAs 150 ppm	STELs 200 ppm TWAs (VLA-EDs) 150 ppm

Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

CAS #	Hazardous components	Europe	Finland OEL	France VL
67-64-1	Acetone	TWA: 1210 mg/m ³ (500 ppm)		TWA: 1210 mg/m ³ (500 ppm) STEL: 2420 mg/m ³ (1000 ppm)
13463-67-7	Titanium Dioxide			10 mg/m ³ TWA [VME]
123-86-4	N-Butyl Acetate		TWAs 150 ppm	OSTELs (VLCT) 200 ppm TWAs (VME) 150 ppm

CAS #	Hazardous components	Hungary OEL	Ireland OEL	Italy OEL
67-64-1	Acetone	TWA: 1210 mg/m ³ STEL: 2420 mg/m ³	TWA: 1210 mg/m ³ (500 ppm)	TWA: 1210 mg/m ³ (500 ppm)
13463-67-7	Titanium Dioxide		30 mg/m ³ STEL (calculated, total inhalable dust); 12 mg/m ³ STEL (calculated, respirable dust) Ireland - 10 mg/m ³ TWA (total inhalable dust); 4 mg/m ³ TWA (respirable dust)	10 mg/m ³ TWA
123-86-4	N-Butyl Acetate	STELs (CKs) 950 mg/m ³ TWAs (AKs) 950 mg/m ³	STELs 200 ppm TWAs 150 ppm	STEL 200 ppm TWA 150 ppm

CAS #	Hazardous components	South Korea	Latvia OEL	Mexico OEL
67-64-1	Acetone	TWA: 1188 mg/m ³ (500 ppm) STEL: 1782 mg/m ³ (750 ppm)	TWA: 1210 mg/m ³ (500 ppm)	TWA: 2400 mg/m ³ (1000 ppm) STEL: 3000 mg/m ³ (1260 ppm)
13463-67-7	Titanium Dioxide	10 mg/m ³ TWA (Serial No. 461)	10 mg/m ³ TWA	20 mg/m ³ STEL [PPT-CT] (as Ti) TWAs (LMPE-PPTs) 10 mg/m ³ TWA VLE-PPT (as Ti)
123-86-4	N-Butyl Acetate	STELs 200 ppm TWAs 150 ppm	TWAs 200 mg/m ³	STELs (LMPE-CTs) 200 ppm



Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

				TWAs (LMPE-PPTs) 150 ppm
--	--	--	--	-----------------------------

CAS #	Hazardous components	Malaysia OEL	NIOSH	Netherlands OEL
67-64-1	Acetone	TWA: 1187 mg/m3 (500 ppm)	TWA: 250 ppm	TWA: 1210 mg/m3 STEL: 2420 mg/m3
13463-67-7	Titanium Dioxide			
123-86-4	N-Butyl Acetate		STELs 200 ppm TWAs 150 ppm	

CAS #	Hazardous components	New Zealand	OSHA PELs	Poland
67-64-1	Acetone	TWA: 1185 mg/m3 (500 ppm) STEL: 2375 mg/m3 (1000 ppm)	PEL: 1000 ppm	TWA: 600 mg/m3 STEL: 1800 mg/m3
13463-67-7	Titanium Dioxide	10 mg/m3 TWA		10.0 mg/m3 TWA [NDS]
123-86-4	N-Butyl Acetate	STELs 200 ppm TWAs 150 ppm	150ppm	TWAs (NDSs) 200 mg/m3

CAS #	Hazardous components	Sweden OEL	Singapore	Britain EH40
67-64-1	Acetone	TWA: 600 mg/m3 (250 ppm) STEL: 1200 mg/m3 (500 ppm) (15 min)	TWA: 1780 mg/m3 (750 ppm) STEL: 2380 mg/m3 (1000 ppm)	TWA: 1210 mg/m3 (500 ppm) STEL: 3620 mg/m3 (1500 ppm)
13463-67-7	Titanium Dioxide	5 mg/m3 TLV NGV	10 mg/m3 PEL	30 mg/m3 STEL (calculated, total inhalable); 12 mg/m3 STEL (calculated, respirable) 10 mg/m3 TWA (total inhalable); 4 mg/m3 TWA (respirable)
123-86-4	N-Butyl Acetate	STELs (STVs) 150 ppm TLVs (LLVs) 100 ppm	STELs 200 ppm	

Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

CAS #	Hazardous components	Switzerland OEL	Japan OEL	Spain
67-64-1	Acetone	TWA: 1200 mg/m ³ (500 ppm) STEL: 2400 mg/m ³ (1000 ppm)	TWA: 750 ppm	
13463-67-7	Titanium Dioxide			10 mg/m ³ TWA
123-86-4	N-Butyl Acetate			

8.2 Exposure controls:

8.2.1 Appropriate engineering controls:

Local exhaust to minimize exposure to vapor and particulate matter.
Eye bath, safety shower.

8.2.2 Individual protection measures, such as personal protective equipment

Eye/Face protection: Wear safety glasses with side shields or splash proof eye goggles to prevent the possibility of eye contact.

Skin protection: Wear protective gloves (e.g., polyvinyl alcohol, nitrile, PTFE) and lab coat to minimize possibility of skin contact.

Respiratory protection: None expected to be needed under normal conditions. However, use NIOSH approved half mask air purifying respirator, if needed.

Hygienic Practices: DO NOT SMOKE IN WORK AREA! Promptly remove contaminated clothing. Wash immediately if skin becomes contaminated. Do not eat or drink in work area while using this product. Wash thoroughly at the end of the workday, before eating and using the restroom.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	White Liquid		
Odor:	Characteristic Ketone	Odor threshold:	-
pH:	-	Melting point:	-
Boiling range:	56.0°C	Flash point:	-18°C
Evaporation rate:	-	Upper Explosive Limit:	-
		Lower Explosive Limit:	-
Flammability:	Highly flammable liquid and vapor	Vapor Pressure:	-
Vapor density:	4.0	Relative Density:	1.054
Solubility(ies):	Partially miscible in water	Partition coefficient n-octanol/water:	-



Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

Auto-ignition temperature:	407°C	Decomposition temperature:	-
Viscosity:	-		
Explosive properties:	-		
Oxidizing properties:	-		

9.2 Other information:

Miscibility:	-	VOC:	0.72
--------------	---	------	------

Section 10: Stability and reactivity

10.1 Reactivity

-

10.2 Chemical stability

This product is stable under normal conditions.

10.3 Possibility of hazardous reactions

This product is stable under normal conditions.

10.4 Conditions to avoid:

All ignition sources.

10.5 Incompatible materials:

This product is incompatible with strong oxidizing agents, strong bases, strong alkalis, copper, copper alloys, and reducing agents. Acetone may form explosive mixtures with chromic anhydride, chromyl anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide and thioglycol.

10.6 Hazardous decomposition products

Fire may create toxic gases/vapors/fumes of carbon monoxide (CO), carbon dioxide (CO₂) and/or nitrous oxides.

Section 11: Toxicological information

11.1 Information on Toxicological effects

Acute toxicity:

The toxicity of this product has not been tested.

Skin corrosion/irritation:

Skin Contact: Irritating to skin.

Serious eye damage/irritation:

Eye contact: Irritating to eyes.

Safety Data Sheet

Date: 7/18/2019

Product Number: 51-0006-01

Revision: B

Product Name: Ink, Acetone White Opaque

Respiratory or skin sensitization:

Germ cell mutagenicity:

None of the components of this product are considered to be mutagens.

Carcinogenicity:

None of the components of this product are considered to be carcinogens.

Reproductive toxicity:

Not known

STOT-single exposure:

STOT-repeated exposure:

Aspiration hazard

11.1.1 Hazard Class information:

11.1.2 Mixture toxicity:

Inhalation Toxicity LC50: 4,232mg/L

123-86-4 - n-Butyl Acetate: Inhalation LC50: 344 mg/L (rat)

11.1.3 Critical studies:

11.1.4 Non-compliance hazard class:

11.1.5 Information on likely routes of exposure:

11.1.6 Symptoms related to the physical, chemical and toxicological characteristics:

11.1.7 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

11.1.8 Interactive effects:

11.1.9 Absence of specific data:

11.1.10 Mixtures:

11.1.11 Mixture vs Substance information:



Safety Data Sheet

Product Number: 51-0006-01 Date: 7/18/2019
Product Name: Ink, Acetone White Opaque Revision: B

11.1.12 Other information:

Section 12: Ecological information

- 12.1 **Toxicity:** Not determined
- 12.2 **Persistence and degradability:** Not determined
- 12.3 **Bioaccumulative potential:** Not determined
- 12.4 **Mobility in soil:** Not determined
- 12.5 **Results of PBT and vPvB assessment:** Not determined
- 12.6 **Other adverse effects:** Not determined

Section 13: Disposal considerations

13.1 **Waste treatment methods:**

Disposal of at a facility that complies with local, state and federal regulations. DO NOT DISPOSE IN SEWER, WATERWAYS, OR ON GROUND. Do not attempt to recycle by distillation or incinerate empty container due to possible explosion hazards. Empty containers contain product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose to heat, flame, sparks, static electricity, or sources of ignition. They may explode and cause injury or death.

Section 14: Transport information

14.1	UN number:	1210
14.2	Proper shipping name:	
	US DOT:	Printing Ink
	Canadian TDG:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]

Safety Data Sheet

Date: 7/18/2019
 Product Number: 51-0006-01 Revision: B
 Product Name: Ink, Acetone White Opaque

European ADR/RID:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
IMDG/IMO:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
ICAO/IATA:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
14.3 Transport hazard class(es) :	3 - FLAMMABLE LIQUID
14.4 Packing group:	II
14.5 Environmental hazards:	N/A
14.6 Special precautions for user:	N/A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	N/A

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists				
CAS #	Hazardous components	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-64-1	Acetone	No	Yes 5000LB	No
13463-67-7	Titanium Dioxide			
123-86-4	N-Butyl Acetate	No	No	No

CAS #	Hazardous components	Canadian NPRI	Canadian Toxic	Canadian DSL
67-64-1	Acetone	No	No	Yes
13463-67-7	Titanium Dioxide	Yes 1 tonne		Yes
123-86-4	N-Butyl Acetate	Yes 1 tonne		Yes

CAS #	Hazardous components	CAA HAP, ODC	CWA NPDES	TSCA
67-64-1	Acetone	No	No	Yes - Inv
13463-67-7	Titanium Dioxide			Yes
123-86-4	N-Butyl Acetate			Yes

Safety Data Sheet

Date: 7/18/2019
 Product Number: 51-0006-01 Revision: B
 Product Name: Ink, Acetone White Opaque

CAS #	Hazardous components	CA Prop 65	Mexico INSQ	Australia ICS
67-64-1	Acetone	No	Listed	Listed
13463-67-7	Titanium Dioxide	Yes	Listed	Listed
123-86-4	N-Butyl Acetate	No	Listed	Listed

CAS #	Hazardous components	New Zealand IOC	China IECSC	Japan ENCS
67-64-1	Acetone	Listed	Listed	Yes - 2-542
13463-67-7	Titanium Dioxide	Listed	Listed	Yes
123-86-4	N-Butyl Acetate	Listed	Listed	Yes

CAS #	Hazardous components	Japan ISHL	Korea ECL	Philippines
67-64-1	Acetone	No	Yes KE-29367	Listed
13463-67-7	Titanium Dioxide	Yes	Yes	Listed
123-86-4	N-Butyl Acetate	Yes	Yes	Listed

CAS #	Hazardous components	Taiwan TCSCA	Singapore HSL	Israel HSL:
67-64-1	Acetone	Listed	No	No
13463-67-7	Titanium Dioxide	Listed		
123-86-4	N-Butyl Acetate	Listed		

CAS #	Hazardous components	Germany WHCS	Switzerland Giftliste 1	Switzerland INNS
67-64-1	Acetone	Yes – 150	Yes G-2429	No
13463-67-7	Titanium Dioxide			
123-86-4	N-Butyl Acetate			

CAS #	Hazardous components	REACH	Kyoto GHG	Rotterdam
67-64-1	Acetone	Yes - (R), (P)	No	No
13463-67-7	Titanium Dioxide			
123-86-4	N-Butyl Acetate	No		

CAS #	Hazardous components	Stockholm		
67-64-1	Acetone	No		
13463-67-7	Titanium Dioxide			
123-86-4	N-Butyl Acetate			



Safety Data Sheet

Date: 7/18/2019
Product Number: 51-0006-01 Revision: B
Product Name: Ink, Acetone White Opaque

15.2 Chemical safety assessment

Section 16: Other information

Revision Date: 7/18/2019

Revision Notes: Rev B: Format updated to (EU) 2015/830.

Additional Information:

Company Disclaimer:

The information and recommendations contained herein are, to the best of BestCode's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, BestCode recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not-permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, date and information furnished by BestCode hereunder are given gratis and BestCode assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.