

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2015/830

## **Section 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product Identifier**

Product Name: Ink, White PL Opaque

Product Code: 51-0055-01

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Product Use: Printing ink for use in BestCode CIJ

### **1.3 Details of the supplier of the safety data sheet**

BestCode

3034 SE Loop 820

Fort Worth, TX 76140

817-349-8555

**For further information, please contact Customer Service:**

Customer Service: 817-349-8555

Email: Info@Bestcode.co

### **1.4 Emergency telephone number**

Emergency Contact: Local Poison Information Center

Chem Tel. Inc. Toll Free 800-255-3924

International 813-248-0585

## **Section 2: Hazards identification**

### **2.1 Classification of the mixture in accordance with Article 40 of Regulation (EC) No 1272/2008**

#### **GHS Rating:**

Flammable Liquids, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

### **2.2 Label elements**



Signal word: Danger

# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

## Hazard statements:

H225 - Highly flammable liquid and vapor.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

EUH066 - Repeated exposure may cause skin dryness or cracking.

## Precautionary statements:

P233 - Keep container tightly closed.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P243 - Take precautionary measures against static discharge.

P242 - Use only non-sparking tools.

P271 - Use only outdoors or in a well-ventilated area.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P370+378 - In case of fire, use ... to extinguish.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER/doctor/...

P309+311 - Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P403+235 - Store in cool/well-ventilated place.

P501 - Dispose of contents/container to ...

P405 - Store locked up.

P403+233 - Store container tightly closed in well-ventilated place.

## 2.3 Other Hazards

No data available.

# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

## Section 3: Composition/information on ingredients

### 3.1 Substances:

### 3.2 Mixtures:

CAS #	EC #	Hazardous components / REACH Registration No.	Concentration	GHS Classification
78-93-3	201-159-0	Methyl Ethyl Ketone	40 - 70%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
97-64-3	202-598-0 607-129-00-7	Propanoic acid, 2-Hydroxy-, ethyl ester	1 - 5%	Flam. Liq. 3: H226 Eye Damage 1: H318 STOT (SE) 3: H335

## Section 4: First Aid Measures

### 4.1 Description of first aid measures

- Inhalation** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid. If breathed in, move person into fresh air. If not breathing give artificial respiration.
- Eyes:** In case of contact, immediately flush eyes with plenty of water for a t least 15 minutes. Get medical aid. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
- Skin:** In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse. Wash off with soap and plenty of water. Consult a physician.
- Ingestion:** Potential for aspiration if swallowed. Get medical aid immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward. Do NOT induce vomiting. Rinse mouth with water. Consult a physician.

### 4.2 Most Important symptoms and effects, both acute and delayed

- Inhalation** Causes respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. May cause central nervous system effects such as nausea and headache. Neurobehavioural effects of exposure to MEK (200 ppm for 4 hrs)

## Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

were studied with 137 volunteers. There were no statistically significant effects observed in biochemical, psychomotor, sensorimotor and psychological tests. May be harmful if inhaled.

Chronic inhalation may cause effects similar to those of acute inhalation.

Chronic overexposure to vapors may cause lung damage.

**Eye contact** Causes eye irritation. Vapors may cause eye irritation. Animal evidence suggests that MEK is a moderate to severe eye irritant.

**Skin contact** May be absorbed through the skin in harmful amounts. Repeated or prolonged exposure may cause drying and cracking of the skin. Only one human case of skin sensitization was located. Negative results were obtained in an animal test; MEK did not produce skin sensitization in the mouse ear thickness test. May be harmful if absorbed through the skin. Causes skin irritation.

Prolonged or repeated skin contact may cause defatting and dermatitis. Animal studies have reported that fetal effects/abnormalities may occur when maternal toxicity is seen.

**Ingestion** May cause irritation of the digestive tract. Possible aspiration hazard. May cause central nervous system depression. Animal evidence suggests that MEK can be aspirated (inhaled) into the lungs during ingestion or vomiting. May be harmful if swallowed.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to doctor:** Treat symptomatically and supportively. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

## **Section 5: Fire Fighting Measures**

### **5.1 Extinguishing media**

In case of fire, use carbon dioxide, dry chemical powder or appropriate foam. Water may be ineffective because it will not cool material below its flash point. For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

### **5.2 Special hazards arising from the substance or mixture**

Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

### **5.3 Advice for firefighters**

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

Wear self contained breathing apparatus for fire fighting if necessary.

Further information.

Use water spray to cool unopened containers.

## **Section 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

Avoid contact with skin and eyes. Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Use proper personal protective equipment as indicated in Section 8.

#### **6.1.2 For emergency responders**

Avoid contact with skin and eyes. Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Use proper personal protective equipment as indicated in Section 8.

## 6.2 Environmental Precautions

Advise local authorities if large spills cannot be contained. Do not allow product to enter drains. Prevent further spillage if safe.

## 6.3 Methods and material for containment and cleaning up

### 6.3.1 For Containment:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

### 6.3.2 Clean up and disposal of spill:

Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. Personal precautions.

## Section 7: Handling and storage

### 7.1 Precautions for safe handling

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, sparks and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor. Avoid inhalation of vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

### 7.2 Conditions for safe storage, including any compatibilities

Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area. Keep container tightly closed in a dry and well-ventilated place. Store in cool place.

### 7.3 Specific end use(s)

Fluid delivery to BestCode Series 8 CIJ. Follow safety instructions outlined in 7.1 & 7.2 while handling. Observe warnings provided with BestCode Series 8 CIJ system when installing and handling fluids.



# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

## Section 8: Exposure control/personal protection

### 8.1 Control parameters

CAS #	Hazardous components	ACGIH TLV	Australia	Austria
78-93-3	Methyl Ethyl Ketone	200 ppm/8 hour		TWAs - 100 ppm
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Belgium OEL	California, USA	Ontario, CA
78-93-3	Methyl Ethyl Ketone	200 ppm TWA	PELs 200 ppm STELs 300 ppm	STELs 300 ppm PELs 200 ppm
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	China	Québec, CA	German AGS
78-93-3	Methyl Ethyl Ketone		STELs 100 ppm PELs 50 ppm	
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Germany MAK/TRK	Denmark OEL	Spain OEL
78-93-3	Methyl Ethyl Ketone	200 ppm TWA	50 ppm TWA	
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Europe	Finland OEL	France VL
78-93-3	Methyl Ethyl Ketone		STELs 100 ppm	300 ppm STEL 200 ppm TWA
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Hungary OEL	Ireland OEL	Italy OEL
78-93-3	Methyl Ethyl Ketone	900 mg/m <sup>3</sup> STEL 600 mg/m <sup>3</sup> TWA	300 ppm STEL 200 ppm TWA	300 ppm STEL 200 ppm TWA

# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			
---------	---	--	--	--

CAS #	Hazardous components	South Korea	Latvia OEL	Mexico OEL
78-93-3	Methyl Ethyl Ketone	STELs 300 ppm TWAs 200 ppm	300 ppm STEL 67 ppm TWA	300 ppm STEL 200 ppm TWA
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Malaysia OEL	NIOSH	Netherlands OEL
78-93-3	Methyl Ethyl Ketone		STELs 300 ppm TWAs 200 ppm	
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	New Zealand	OSHA PELs	Poland
78-93-3	Methyl Ethyl Ketone	STELs 300 ppm TWAs 150 ppm	200 ppm/8 hour	STELs 900 mg/m <sup>3</sup> TWAs 450 mg/m <sup>3</sup>
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Sweden OEL	Singapore	Britain EH40
78-93-3	Methyl Ethyl Ketone		PELs 200 ppm STELs 300 ppm	
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

## 8.2 Exposure controls:

### 8.2.1 Appropriate engineering controls:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ventilation fans and other electrical service must be non-sparking and have an explosion-proof design.



# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

## 8.2.2 Individual protection measures, such as personal protective equipment

Wear appropriate protective clothing to prevent skin exposure. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Eye/Face protection:** Wear chemical splash goggles. Face shield and safety glasses.

**Skin protection:** Wear appropriate protective gloves to prevent skin exposure. Handle with gloves.

**Respiratory protection:** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

**Hygienic Practices:** DO NOT SMOKE IN WORK AREA! Promptly remove contaminated clothing. Wash immediately if skin becomes contaminated. Do not eat or drink in work area while using this product. Wash thoroughly at the end of the workday, before eating and using the restroom.

## Section 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	White liquid		
<b>Odor:</b>	Solvent	<b>Odor threshold:</b>	No data available
<b>pH:</b>	No data available	<b>Melting point:</b>	-87.00 C - 15.00 C
<b>Boiling range:</b>	80.00 C - 154.00 C	<b>Flash point:</b>	-7°C
<b>Evaporation rate:</b>	4.6 (BuAC=1)	<b>Upper Explosive Limit:</b>	No data available
		<b>Lower Explosive Limit:</b>	No data available
<b>Flammability:</b>	No data available	<b>Vapor Pressure:</b>	85 MM_HG at 20.0 C
<b>Vapor density:</b>	> Air	<b>Relative Density:</b>	0.936 (H2O = 1 @ 20 °C)
<b>Solubility(ies):</b>	Miscible	<b>Partition coefficient n-octanol/water:</b>	No data available



# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

<b>Auto-ignition temperature:</b>	400.00 C	<b>Decomposition temperature:</b>	No data available
<b>Viscosity:</b>	No data available		No data available
<b>Explosive properties:</b>	> 55.0% Volatile by volume.		
<b>Oxidizing properties:</b>	No data available		

## 9.2 Other information:

<b>Miscibility:</b>	No data available	<b>VOC:</b>	No data available
---------------------	-------------------	-------------	-------------------

## Section 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Will not occur

### 10.4 Conditions to avoid:

ignition sources, Excess heat, Heat, flames and sparks.

### 10.5 Incompatible materials:

Strong oxidizing agents, Strong acids, 2-propanol, Strong oxidizing agents.

### 10.6 Hazardous decomposition products

Carbon monoxide, Carbon dioxide, formed under fire conditions. Carbon oxides.

## Section 11: Toxicological information

### 11.1 Information on Toxicological effects

<b>Acute toxicity:</b>	No data available
<b>Skin corrosion/irritation:</b>	No data available
<b>Serious eye damage/irritation:</b>	No data available
<b>Respiratory or skin sensitization:</b>	No data available
<b>Germ cell mutagenicity:</b>	No data available

## Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

**Carcinogenicity:**

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.  
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.  
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.  
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Reproductive toxicity:**

No data available

**STOT-single exposure:**

No data available

**STOT-repeated exposure:**

No data available

**Aspiration hazard**

No data available

**11.1.1 Hazard Class information:**

No data available

**11.1.2 Mixture toxicity:**

**Methyl Ethyl Ketone**

Inhalation Rat LC50/8 h: 23500 mg/m<sup>3</sup>

Oral Rat LD50: 2737 mg/kg

Oral Mouse LD50: 2190 mg/kg

Dermal Rabbit LD50: 6480 mg/kg

**11.1.3 Critical studies:**

No data available

**11.1.4 Non-compliance hazard class:**

No data available

**11.1.5 Information on likely routes of exposure:**

No data available

**11.1.6 Symptoms related to the physical, chemical and toxicological characteristics:**

No data available

**11.1.7 Delayed and immediate effects as well as chronic effects from short and long-term exposure:**

## Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

No data available

### 11.1.8 Interactive effects:

No data available

### 11.1.9 Absence of specific data:

No data available

### 11.1.10 Mixtures:

No data available

### 11.1.11 Mixture vs Substance information:

No data available

### 11.1.12 Other information:

No data available

## Section 12: Ecological information

### 12.1 Toxicity:

Environmental: Substance evaporates in water with T1/2= 3D (rivers) to 12D (lakes). Substance is not expected to bioconcentrate in marine life. Physical: Substance photodegrades in air with T1/2 = 2.3 days. Oxidizes rapidly by photo-chemical reactions in air. Readily biodegradable meeting the 10-day window criterion. Not expected to bioaccumulate significantly.

### 12.2 Persistence and degradability:

No data available

### 12.3 Bioaccumulative potential:

No data available

### 12.4 Mobility in soil:

No data available

### 12.5 Results of PBT and vPvB assessment:

No data available

### 12.6 Other adverse effects:

No data available



# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

## Section 13: Disposal considerations

### 13.1 Waste treatment methods:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series:

CAS# 78-93-3: waste number U159 (Ignitable waste, Toxic waste). Product.

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber.

Observe all federal, state, and local environmental regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

## Section 14: Transport information

14.1	<b>UN number:</b>	1210
14.2	<b>Proper shipping name:</b>	
	<b>US DOT:</b>	Printing Ink
	<b>Canadian TDG:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	<b>European ADR/RID:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	<b>IMDG/IMO:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	<b>ICAO/IATA:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
14.3	<b>Transport hazard class(es) :</b>	3 - FLAMMABLE LIQUID
14.4	<b>Packing group:</b>	II
14.5	<b>Environmental hazards:</b>	N/A

# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

14.6	Special precautions for user:	N/A
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	N/A

## Section 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists				
CAS #	Hazardous components	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
78-93-3	Methyl Ethyl Ketone	No	Yes 5000 LB	No
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester	No	No	No

CAS #	Hazardous components	Canadian NPRI	Canadian Toxic	Canadian DSL
78-93-3	Methyl Ethyl Ketone	1 tonne	No	Listed
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester	No	No	Listed

CAS #	Hazardous components	CAA HAP, ODC	CWA NPDES	TSCA
78-93-3	Methyl Ethyl Ketone	No	No	Yes - Inventory
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester	No	No	Yes - Inventory

CAS #	Hazardous components	CA Prop 65	Mexico INSQ	Australia ICS
78-93-3	Methyl Ethyl Ketone	No	Listed	Listed
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester	No		

CAS #	Hazardous components	New Zealand IOC	China IECSC	Japan ENCS
78-93-3	Methyl Ethyl Ketone	Listed	Listed	Yes - 2-542

# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester		Listed	Yes - 2-1371
---------	---	--	--------	--------------

CAS #	Hazardous components	Japan ISHL	Korea ECL	Philippines
78-93-3	Methyl Ethyl Ketone	Listed	Listed	Listed
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Taiwan TCSCA	Singapore HSL	Israel HSL:
78-93-3	Methyl Ethyl Ketone	Listed		
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	Germany WHCS	Switzerland Giftliste 1	Switzerland INNS
78-93-3	Methyl Ethyl Ketone			
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

CAS #	Hazardous components	REACH	Kyoto GHG	Rotterdam
78-93-3	Methyl Ethyl Ketone	Yes - (R), (P)		
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester	Yes - (P)		

CAS #	Hazardous components	Stockholm		
78-93-3	Methyl Ethyl Ketone			
97-64-3	Propanoic acid, 2-Hydroxy-, ethyl ester			

# Safety Data Sheet

Date: 5/30/2018

Product Number: 51-0055-01

Revision:

Product Name: Ink, White PL Opaque

## Canadian WHMIS Classification:



CLASS B, DIVISION 2: Flammable Liquids

CLASS D, DIVISION 2, SUBDIVISION B: Toxic Materials (Mutagenicity, skin sensitization, irritation, etc.)

## 15.2 Chemical safety assessment

### Section 16: Other information

**Revision Date:** 5/30/2018

**Revision Notes:**

**Additional Information:**

#### **Company Disclaimer:**

The information and recommendations contained herein are, to the best of BestCode's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, BestCode recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not-permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, date and information furnished by BestCode hereunder are given gratis and BestCode assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.