

# Safety Data Sheet

Product Number: 51-0046-01      Date: 5/21/2020  
Product Name: Ink, Eth Flex Caustic Washable      Revision: A

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2015/830

## **Section 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product Identifier**

Product Name: Ink, Eth Flex Caustic Washable  
Product Code: 51-0046-01

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Product Use: Printing ink for use in BestCode CIJ

### **1.3 Details of the supplier of the safety data sheet**

BestCode  
3034 SE Loop 820  
Fort Worth, TX 76140  
817-349-8555

#### **For further information, please contact Customer Service:**

Customer Service: 817-349-8555  
Email: Info@Bestcode.co

### **1.4 Emergency telephone number**

Emergency Contact: Local Poison Information Center  
Chem Tel. Inc. Toll Free 800-255-3924  
International 813-248-0585

## **Section 2: Hazards identification**

### **2.1 Classification of the mixture in accordance with Article 40 of Regulation (EC) No 1272/2008**

#### **GHS Rating:**

Flammable Liquids, Category 2  
Serious Eye Damage/Eye Irritation, Category 2

### **2.2 Label elements**



Signal word: Danger



# Safety Data Sheet

Date: 5/21/2020

Product Number: 51-0046-01

Revision: A

Product Name: Ink, Eth Flex Caustic Washable

## Hazard statements:

H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation.

## Precautionary statements:

P233 - Keep container tightly closed.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P243 - Take precautionary measures against static discharge.

P242 - Use only non-sparking tools.

P370+378 - In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313 - If eye irritation persists, get medical advice/attention.

P403+235 - Store in cool/well-ventilated place.

P501 - Dispose of contents/container in accordance with local regulations.

## 2.3 Other Hazards

## Section 3: Composition/information on ingredients

### 3.1 Substances:

### 3.2 Mixtures:

CAS #	EC #	Hazardous components / REACH Registration No.	Concentration	GHS Classification
64-17-5	200-578-6 603-002-00-5	Ethyl alcohol	50.0-75.0%	Flam. Liq. 2: H225;
67-63-0	200-661-7 603-117-00-0	Isopropyl alcohol	5.0 -10.0 %	Flam. Liq. 2: H225 Eye Damage 2: H319 STOT (SE) 3: H335 H336
109-60-4	203-686-1	Propyl acetate	1.0 -5.0 %	Flam. Liq. 2: H225; Eye Irrit. 2A: H319; STOT SE 3: H336;
71-23-8	200-746-9	n-Propanol	1.0 -5.0 %	Flam. Liq. 2: H225; Eye Dam. 1: H318; STOT SE 3: H336;

## Section 4: First Aid Measures

### 4.1 Description of first aid measures

- General Notes** Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.
- Inhalation** If breathing is irregular or stopped, immediately seek medical assistance, and start first aid actions. Provide fresh air.
- Eyes:** Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
- Skin:** Wash with plenty of soap and water.
- Ingestion:** Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most Important symptoms and effects, both acute and delayed

- Inhalation** No Data Available  
**Eye contact** No Data Available  
**Skin contact** No Data Available  
**Ingestion** No Data Available

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to doctor:** No Data Available

## Section 5: Fire Fighting Measures

### 5.1 Extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>). Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products  
Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

# Safety Data Sheet

Product Number: 51-0046-01      Date: 5/21/2020  
Product Name: Ink, Eth Flex Caustic Washable      Revision: A

## 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## Section 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Remove persons to safety.

#### 6.1.2 For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental Precautions

Keep away from drains, surface, and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

#### 6.3.1 For Containment:

Covering of drains.

#### 6.3.2 Clean up and disposal of spill:

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal Binder. Place in appropriate containers for disposal. Ventilate affected area.

## Section 7: Handling and storage

### 7.1 Precautions for safe handling

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapors into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion- proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.



# Safety Data Sheet

Date: 5/21/2020

Product Number: 51-0046-01

Revision: A

Product Name: Ink, Eth Flex Caustic Washable

Vapors may form explosive mixtures with air. Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feeding stuffs.

## 7.2 Conditions for safe storage, including any compatibilities

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight. Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight. Use local and general ventilation. Ground/bond container and receiving equipment. Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

## 7.3 Specific end use(s)

Fluid delivery to BestCode Series 8 CIJ. Follow safety instructions outlined in 7.1 & 7.2 while handling. Observe warnings provided with BestCode Series 8 CIJ system when installing and handling fluids.

## Section 8: Exposure control/personal protection

### 8.1 Control parameters

CAS #	Hazardous components	ACGIH TLV	Australia	Austria
64-17-5	Ethyl alcohol	TLV: 1000 ppm	TWA: 1900 mg/m3 (1000 ppm) STEL: 3800 mg/m3 (2000 ppm)	TWA: 1880 mg/m3 (1000 ppm)
67-63-0	Isopropyl alcohol	TLV: 200 ppm STEL: 400 ppm	TWA: 500 mg/m3 (200 ppm) STEL: 2000 mg/m3 (800 ppm)	TWA: 983 mg/m3 (400 ppm) STEL: 1230 mg/m3 (500 ppm)
109-60-4	Propyl acetate	TWA: 100 ppm STEL: 150 ppm		

CAS #	Hazardous components	Belgium OEL	California, USA	Ontario, CA
64-17-5	Ethyl alcohol	TWA: 1907 mg/m3 (1000 ppm)	TWA: 1900 mg/m3 (1000 ppm)	STEL: 1000 ppm
67-63-0	Isopropyl alcohol	TWA: 500 mg/m3 (200 ppm) STEL: 1000 mg/m3 (400 ppm)	TWA: 980 mg/m3 (400 ppm) STEL: 1225 mg/m3 (500 ppm)	TWA: 200 ppm STEL: 400 ppm
109-60-4	Propyl acetate			TWA: 200 ppm



# Safety Data Sheet

Date: 5/21/2020

Product Number: 51-0046-01

Revision: A

Product Name: Ink, Eth Flex Caustic Washable

				STEL: 250 ppm
--	--	--	--	---------------

CAS #	Hazardous components	China	Québec, CA	German AGS
64-17-5	Ethyl alcohol		TWA: 1880 mg/m <sup>3</sup> (1000 ppm)	TWA: 960 mg/m <sup>3</sup> (500 ppm) STEL: 1920 mg/m <sup>3</sup> (1000 ppm) (15 min)
67-63-0	Isopropyl alcohol	TWA: 350 mg/m <sup>3</sup> STEL: 700 mg/m <sup>3</sup> (15 min)	TWA: 983 mg/m <sup>3</sup> (400 ppm) STEL: 1230 mg/m <sup>3</sup> (500 ppm)	TWA: 500 mg/m <sup>3</sup> (200 ppm) STEL: 1000 mg/m <sup>3</sup> (400 ppm) (15 min)
109-60-4	Propyl acetate			

CAS #	Hazardous components	Germany MAK/TRK	Denmark OEL	Spain OEL
64-17-5	Ethyl alcohol	TWA: 1900 mg/m <sup>3</sup> (1000 ppm) STEL: 3800 mg/m <sup>3</sup> (2000 ppm) (60min) (3x) TWA: 960 mg/m <sup>3</sup> (500 ppm)	TWA: 1900 mg/m <sup>3</sup> (1000 ppm) STEL: 3800 mg/m <sup>3</sup> (2000 ppm)	STEL: 1910 mg/m <sup>3</sup> (1000 ppm)
67-63-0	Isopropyl alcohol	TWA: 500 mg/m <sup>3</sup> (200 ppm) STEL: 2000 mg/m <sup>3</sup> (15/30min)(4x) (800 ppm 15/30min) (4x)	TWA: 500 mg/m <sup>3</sup> (200 ppm) STEL: 980 mg/m <sup>3</sup> (400 ppm)	TWA: 500 mg/m <sup>3</sup> (200 ppm) STEL: 1000 mg/m <sup>3</sup> (400ppm)
109-60-4	Propyl acetate			

CAS #	Hazardous components	Europe	Finland OEL	France VL
64-17-5	Ethyl alcohol		TWA: 1900 mg/m <sup>3</sup> (1000 ppm) STEL: 2500 mg/m <sup>3</sup> (1300 ppm) (15 min)	TWA: 1900 mg/m <sup>3</sup> (1000 ppm) STEL: 9500 mg/m <sup>3</sup> (5000 ppm)
67-63-0	Isopropyl alcohol		TWA: 500 mg/m <sup>3</sup> (200 ppm) STEL: 620 mg/m <sup>3</sup> (250 ppm) (15 min)	STEL: 980 mg/m <sup>3</sup> (400 ppm)
109-60-4	Propyl acetate			



# Safety Data Sheet

Date: 5/21/2020

Product Number: 51-0046-01

Revision: A

Product Name: Ink, Eth Flex Caustic Washable

CAS #	Hazardous components	Hungary OEL	Ireland OEL	Italy OEL
64-17-5	Ethyl alcohol	TWA: 1900 mg/m <sup>3</sup> STEL: 7600 mg/m <sup>3</sup>	STEL: 1000 ppm (15 min)	
67-63-0	Isopropyl alcohol	TWA: 500 mg/m <sup>3</sup> STEL: 2000 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm (15 min)	
109-60-4	Propyl acetate			

CAS #	Hazardous components	South Korea	Latvia OEL	Mexico OEL
64-17-5	Ethyl alcohol	TWA: 1900 mg/m <sup>3</sup> (1000 ppm)	TWA: 1000 mg/m <sup>3</sup>	TWA: 1900 mg/m <sup>3</sup> (1000 ppm)
67-63-0	Isopropyl alcohol	TWA: 480 mg/m <sup>3</sup> (200 ppm) STEL: 980 mg/m <sup>3</sup> (400 ppm)	TWA: 350 mg/m <sup>3</sup> STEL: 600 mg/m <sup>3</sup> (15 min)	TWA: 980 mg/m <sup>3</sup> (400 ppm) STEL: 1225 mg/m <sup>3</sup> (500 ppm)
109-60-4	Propyl acetate			TWA/VLE-PPT: 200 ppm TWA/VLE-PPT: 840 mg/m <sup>3</sup> STEL/PPT-CT: 250 ppm STEL/PPT-CT: 1050 mg/m <sup>3</sup>

CAS #	Hazardous components	Malaysia OEL	NIOSH	Netherlands OEL
64-17-5	Ethyl alcohol	TWA: 1880 mg/m <sup>3</sup> (1000 ppm)	TWA: 1900 mg/m <sup>3</sup> (1000 ppm)	TWA: 260 mg/m <sup>3</sup> STEL: 1900 mg/m <sup>3</sup>
67-63-0	Isopropyl alcohol	TWA: 983 mg/m <sup>3</sup> (400 ppm)	TWA: 980 mg/m <sup>3</sup> (400 ppm) STEL: 1225 mg/m <sup>3</sup> (500 ppm)	
109-60-4	Propyl acetate			

CAS #	Hazardous components	New Zealand	OSHA PELs	Poland
64-17-5	Ethyl alcohol	TWA: 1880 mg/m <sup>3</sup> (1000 ppm)	PEL: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
67-63-0	Isopropyl alcohol	TWA: 983 mg/m <sup>3</sup> (400 ppm) STEL: 1230 mg/m <sup>3</sup> (500 ppm)	PEL: 400 ppm	TWA: 900 mg/m <sup>3</sup> STEL: 1200 mg/m <sup>3</sup>
109-60-4	Propyl acetate		TWA: 200 ppm TWA: 840 mg/m <sup>3</sup>	



# Safety Data Sheet

Date: 5/21/2020

Product Number: 51-0046-01

Revision: A

Product Name: Ink, Eth Flex Caustic Washable

			STEL: 250 ppm STEL: 1050 mg/m3	
--	--	--	-----------------------------------	--

CAS #	Hazardous components	Sweden OEL	Singapore	Britain EH40
64-17-5	Ethyl alcohol	TWA: 1000 mg/m3 (500 ppm) STEL: 1900 mg/m3 (1000 ppm) (15 min)	TWA: 1880 mg/m3 (1000 ppm)	TWA: 1920 mg/m3 (1000 ppm)
67-63-0	Isopropyl alcohol	TWA: 350 mg/m3 (150 ppm) STEL: 600 mg/m3 (250 ppm) (15 min)	TWA: 983 mg/m3 (400 ppm) STEL: 1230 mg/m3 (500 ppm)	TWA: 999 mg/m3 (400 ppm) STEL: 1250 mg/m3 (500 ppm)
109-60-4	Propyl acetate			

CAS #	Hazardous components	Switzerland OEL	Japan OEL	
64-17-5	Ethyl alcohol			
67-63-0	Isopropyl alcohol	TWA: 500 mg/m3 (200 ppm) STEL: 1000 mg/m3 (400 ppm)		
109-60-4	Propyl acetate			

## 8.2 Exposure controls:

### 8.2.1 Appropriate engineering controls:

General ventilation.

### 8.2.2 Individual protection measures, such as personal protective equipment

#### Eye/Face protection:

Wear eye/face protection.

#### Skin protection:

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leaktightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Take recovery periods for skin regeneration. Preventive skin protection (barrier creams, ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection

#### Hygienic Practices:

DO NOT SMOKE IN WORK AREA! Promptly remove contaminated clothing. Wash immediately if skin becomes contaminated. Do not eat



# Safety Data Sheet

Product Number: 51-0046-01      Date: 5/21/2020  
 Product Name: Ink, Eth Flex Caustic Washable      Revision: A

or drink in work area while using this product. Wash thoroughly at the end of the workday, before eating and using the restroom.

## Section 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Appearance:</b>	Dark Liquid		
<b>Odor:</b>	Pungent	<b>Odor threshold:</b>	No data available
<b>pH:</b>		<b>Melting point:</b>	
<b>Boiling range:</b>	64.7 °C at 1,013 hPa	<b>Flash point:</b>	9.7 °C at 1,013 hPa 49.46 °F at 1,013 hPa
<b>Evaporation rate:</b>	5.8 (BuAC=1)	<b>Upper Explosive Limit:</b>	13.5 vol%
		<b>Lower Explosive Limit:</b>	2.5 vol%
<b>Flammability:</b>	No data available	<b>Vapor Pressure:</b>	169.3 hPa at 25 °C
<b>Vapor density:</b>	> Air	<b>Relative Density:</b>	0.841
<b>Solubility(ies):</b>		<b>Partition coefficient n-octanol/water:</b>	No data available
<b>Auto-ignition temperature:</b>	380 C	<b>Decomposition temperature:</b>	No data available
<b>Viscosity:</b>			
<b>Explosive properties:</b>	None		
<b>Oxidizing properties:</b>	None		

### 9.2 Other information:

<b>Miscibility:</b>	No data available	<b>VOC:</b>	5.93 lb/gal
---------------------	-------------------	-------------	-------------

## Section 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition if heated.

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

## 10.5 Incompatible materials:

Oxidizers

## 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## Section 11: Toxicological information

### 11.1 Information on Toxicological effects

<b>Acute toxicity:</b>	Shall not be classified as acutely toxic.
<b>Skin corrosion/irritation:</b>	Shall not be classified as corrosive/irritant to skin.
<b>Serious eye damage/irritation:</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization:</b>	Shall not be classified as a respiratory or skin sensitizer.
<b>Germ cell mutagenicity:</b>	Shall not be classified as germ cell mutagenic.
<b>Carcinogenicity:</b>	Shall not be classified as carcinogenic.
<b>Reproductive toxicity:</b>	Shall not be classified as a reproductive toxicant.
<b>STOT-single exposure:</b>	Shall not be classified as a specific target organ toxicant (single exposure).
<b>STOT-repeated exposure:</b>	Shall not be classified as a specific target organ toxicant (repeated exposure).
<b>Aspiration hazard</b>	Shall not be classified as presenting an aspiration hazard.

#### 11.1.1 Hazard Class information:

No data available

#### 11.1.2 Mixture toxicity:

No data available

#### 11.1.3 Critical studies:

No data available

#### 11.1.4 Non-compliance hazard class:

No data available

#### 11.1.5 Information on likely routes of exposure:

No data available

#### 11.1.6 Symptoms related to the physical, chemical and toxicological characteristics:

No data available



# Safety Data Sheet

Product Number: 51-0046-01      Date: 5/21/2020  
Product Name: Ink, Eth Flex Caustic Washable      Revision: A

**11.1.7 Delayed and immediate effects as well as chronic effects from short and long-term exposure:**

No data available

**11.1.8 Interactive effects:**

No data available

**11.1.9 Absence of specific data:**

No data available

**11.1.10 Mixtures:**

No data available

**11.1.11 Mixture vs Substance information:**

No data available

**11.1.12 Other information:**

No data available

## **Section 12: Ecological information**

**12.1 Toxicity:**

Shall not be classified as hazardous to the aquatic environment.

**12.2 Persistence and degradability:**

No data available

**12.3 Bioaccumulative potential:**

No data available

**12.4 Mobility in soil:**

No data available

**12.5 Results of PBT and vPvB assessment:**

No data available

**12.6 Other adverse effects:**

No data available



# Safety Data Sheet

Product Number: 51-0046-01      Date: 5/21/2020  
 Product Name: Ink, Eth Flex Caustic Washable      Revision: A

## Section 13: Disposal considerations

### 13.1 Waste treatment methods:

**Waste treatment-relevant information**

Solvent reclamation/regeneration.

**Sewage disposal-relevant information**

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

**Waste treatment of containers/packages**

Only packaging's which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities

## Section 14: Transport information

14.1	<b>UN number:</b>	1210
14.2	<b>Proper shipping name:</b>	
	<b>US DOT:</b>	Printing Ink
	<b>Canadian TDG:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	<b>European ADR/RID:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	<b>IMDG/IMO:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	<b>ICAO/IATA:</b>	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
14.3	<b>Transport hazard class(es) :</b>	3 - FLAMMABLE LIQUID
14.4	<b>Packing group:</b>	II
14.5	<b>Environmental hazards:</b>	N/A
14.6	<b>Special precautions for user:</b>	N/A
14.7	<b>Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	
		N/A

# Safety Data Sheet

Product Number: 51-0046-01      Date: 5/21/2020  
 Product Name: Ink, Eth Flex Caustic Washable      Revision: A

## Section 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists				
CAS #	Hazardous components	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
64-17-5	Ethyl alcohol	No	No	No
67-63-0	Isopropyl alcohol	No	No	Yes

CAS #	Hazardous components	Canadian NPRI	Canadian Toxic	Canadian DSL
64-17-5	Ethyl alcohol	Yes	No	Yes
67-63-0	Isopropyl alcohol	Yes	No	Yes

CAS #	Hazardous components	CAA HAP, ODC	CWA NPDES	TSCA
64-17-5	Ethyl alcohol	No	No	Yes - Inv
67-63-0	Isopropyl alcohol	No	No	Yes - Inv

CAS #	Hazardous components	CA Prop 65	Mexico INSQ	Australia ICS
64-17-5	Ethyl alcohol	No	Yes	Yes
67-63-0	Isopropyl alcohol	No	Yes 1219	Yes

CAS #	Hazardous components	New Zealand IOC	China IECSC	Japan ENCS
64-17-5	Ethyl alcohol	Yes	Yes	Yes 5-153
67-63-0	Isopropyl alcohol	Yes	Yes	Yes 2-207

CAS #	Hazardous components	Japan ISHL	Korea ECL	Philippines
64-17-5	Ethyl alcohol	No	Yes KE-13217	Yes
67-63-0	Isopropyl alcohol	Yes -2-(8)-319	Yes KE-29363	Yes

CAS #	Hazardous components	Taiwan TCSCA	Singapore HSL	Israel HSL:
64-17-5	Ethyl alcohol	Yes	No	Yes-Cat.
67-63-0	Isopropyl alcohol	Yes	No	Yes - Cat



# Safety Data Sheet

Date: 5/21/2020

Product Number: 51-0046-01

Revision: A

Product Name: Ink, Eth Flex Caustic Washable

CAS #	Hazardous components	Germany WHCS	Switzerland Giftliste 1	Switzerland INNS
64-17-5	Ethyl alcohol	Yes 96	Yes G-1158	No
67-63-0	Isopropyl alcohol	Yes – 135	Yes G-1712	No

CAS #	Hazardous components	REACH	Kyoto GHG	Rotterdam
64-17-5	Ethyl alcohol	Yes – (R),(P)	No	No
67-63-0	Isopropyl alcohol	Yes – (R),(P)	No	No

CAS #	Hazardous components	Stockholm		
64-17-5	Ethyl alcohol	No		
67-63-0	Isopropyl alcohol	No		

## 15.2 Chemical safety assessment

## Section 16: Other information

**Revision Date:** 5/21/2020

**Revision Notes:** Format updated to (EU) 2015/830.

**Additional Information:**

### **Company Disclaimer:**

The information and recommendations contained herein are, to the best of BestCode's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, BestCode recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not-permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, date and information furnished by BestCode hereunder are given gratis and BestCode assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.