

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2015/830

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name: Makeup, Alcohol Resistant

Product Code: 52-0032-01

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product Use: Printing ink for use in BestCode CIJ

1.3 Details of the supplier of the safety data sheet

BestCode

3034 SE Loop 820

Fort Worth, TX 76140

817-349-8555

For further information, please contact Customer Service:

Customer Service: 817-349-8555

Email: Info@Bestcode.co

1.4 Emergency telephone number

Emergency Contact: Local Poison Information Center

Chem Tel. Inc. Toll Free 800-255-3924

International 813-248-0585

Section 2: Hazards identification

2.1 Classification of the mixture in accordance with Article 40 of Regulation (EC) No 1272/2008

GHS Rating:

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2

Specific Target Organ Toxicity (single exposure), Category 3

2.2 Label elements



Signal word: Danger

Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

Hazard statements:

H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

Precautionary statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P243 - Take precautionary measures against static discharge.

P242 - Use only non-sparking tools.

P264 - Wash hands thoroughly after handling.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER/doctor if you feel unwell.

P337+313 - If eye irritation persists, get medical advice/attention.

P370+378 - In case of fire, use carbon dioxide, dry chemical powder or appropriate foam to extinguish.

P403+235 - Store in cool/well-ventilated place.

P403+233 - Store container tightly closed in well-ventilated place.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local regulations.

2.3 Other Hazards

Adverse Human Health Effects and Symptoms:

Chronic: Chronic inhalation may cause effects similar to those of acute inhalation.

Prolonged or repeated skin contact may cause defatting and dermatitis. Animal studies have reported that fetal effects/abnormalities may occur when maternal toxicity is seen. Chronic overexposure to vapors may cause lung damage.

Inhalation:

Causes respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. May cause central nervous system effects such as nausea and headache. Neurobehavioural effects of exposure to MEK (200 ppm for 4 hrs) were studied with 137 volunteers. There were no statistically significant effects observed in biochemical, psychomotor, sensorimotor and psychological tests.



Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

Skin Contact:

May be absorbed through the skin in harmful amounts. Repeated or prolonged exposure may cause drying and cracking of the skin. Only one human case of skin sensitization was located. Negative results were obtained in an animal test; MEK did not produce skin sensitization in the mouse ear thickness test.

Eye Contact:

Causes eye irritation. Vapors may cause eye irritation. Animal evidence suggests that MEK is a moderate to severe eye irritant.

Ingestion:

May cause irritation of the digestive tract. Possible aspiration hazard. May cause central nervous system depression. Animal evidence suggests that MEK can be aspirated (inhaled) into the lungs during ingestion or vomiting.

Section 3: Composition/information on ingredients

3.1 Substances:

3.2 Mixtures:

| CAS # | EC # | Hazardous components / REACH Registration No. | Concentration | GHS Classification |
|---------|-----------|---|---------------|--|
| 78-93-3 | 201-159-0 | Methyl Ethyl Ketone | 60.0 – 100.0% | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; EUH066 |

Section 4: First Aid Measures

4.1 Description of first aid measures

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical aid.

Skin: In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

Ingestion: Potential for aspiration if swallowed. Get medical aid immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward.



Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

4.2 Most Important symptoms and effects, both acute and delayed

Inhalation No Data Available

Eye contact No Data Available

Skin contact No Data Available

Ingestion No Data Available

4.3 Indication of any immediate medical attention and special treatment needed

Notes to doctor: Treat symptomatically and supportively.

Section 5: Fire Fighting Measures

5.1 Extinguishing media

In case of fire, use carbon dioxide, dry chemical powder or appropriate foam. Water may be ineffective because it will not cool material below its flash point.

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Extremely flammable liquid and vapor. Vapor may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

No data available

6.1.1 For non-emergency personnel

Use proper personal protective equipment as indicated in Section 8.

6.1.2 For emergency responders

Use proper personal protective equipment as indicated in Section 8.

6.2 Environmental Precautions

No data available.



Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

6.3 Methods and material for containment and cleaning up

6.3.1 For Containment:

Remove all sources of ignition. Use a spark-proof tool. Provide ventilation.

6.3.2 Clean up and disposal of spill:

Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Clean up spills immediately, observing precautions in the Protective Equipment section.

Section 7: Handling and storage

7.1 Precautions for safe handling

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Keep away from heat, sparks and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor.

7.2 Conditions for safe storage, including any compatibilities

Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area..

7.3 Specific end use(s)

Fluid delivery to BestCode Series 8 CIJ. Follow safety instructions outlined in 7.1 & 7.2 while handling. Observe warnings provided with BestCode Series 8 CIJ system when installing and handling fluids.

Section 8: Exposure control/personal protection

8.1 Control parameters

| CAS # | Hazardous components | ACGIH TLV | Australia | Austria |
|---------|----------------------|-------------------------------|---|---|
| 78-93-3 | Methyl Ethyl Ketone | TLV: 200 ppm STEL: 300 ppm | TWA: 295 mg/m ³ (100 ppm) STEL: 590 mg/m ³ (200 ppm) | TWA: 445 mg/m ³ (150 ppm) STEL: 890 mg/m ³ (300 ppm) |

Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

| CAS # | Hazardous components | Belgium OEL | California, USA | Ontario, CA |
|---------|----------------------|---|---|-------------------------------|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm) | TWA: 590 mg/m ³ (200 ppm) STEL: 885 mg/m ³ (300 ppm) | TWA: 200 ppm STEL: 300 ppm |

| CAS # | Hazardous components | China | Québec, CA | German AGS |
|---------|----------------------|--|--|--|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 300 mg/m ³ STEL: 600 mg/m ³ (15 min) | TWA: 150 mg/m ³ (50 ppm) STEL: 300 mg/m ³ (100 ppm) | TWA: 600 mg/m ³ (200 ppm) STEL: 600 mg/m ³ (200 ppm) (15 min) |

| CAS # | Hazardous components | Germany MAK/TRK | Denmark OEL | Spain OEL |
|---------|----------------------|--|--|---|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 295 mg/m ³ (100 ppm) STEL: 600 mg/m ³ (200 ppm) (30min) (4x) | TWA: 145 mg/m ³ (50 ppm) STEL: 290 mg/m ³ (100 ppm) | TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm) |

| CAS # | Hazardous components | Europe | Finland OEL | France VL |
|---------|----------------------|---|--|---|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm) | STEL: 300 mg/m ³ (100 ppm) (15 min) | TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm) |

| CAS # | Hazardous components | Hungary OEL | Ireland OEL | Italy OEL |
|---------|----------------------|---|--|---|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 600 mg/m ³ STEL: 900 mg/m ³ | TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm) (15 min) | TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm) |

| CAS # | Hazardous components | South Korea | Latvia OEL | Mexico OEL |
|---------|----------------------|---|---|---|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 590 mg/m ³ (200 ppm) STEL: 885 mg/m ³ (300 ppm) | TWA: 200 mg/m ³ (67 ppm) STEL: 900 mg/m ³ (300 ppm) (15 min) | TWA: 590 mg/m ³ (200 ppm) STEL: 885 mg/m ³ (300 ppm) |

| CAS # | Hazardous components | Malaysia OEL | NIOSH | Netherlands OEL |
|---------|----------------------|--------------------------------------|-------------------------------|---|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 590 mg/m ³ (200 ppm) | TWA: 200 ppm STEL: 300 ppm | TWA: 590 mg/m ³ STEL: 900 mg/m ³ |



Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

| CAS # | Hazardous components | New Zealand | OSHA PELs | Poland |
|---------|----------------------|---|--------------|---|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 445 mg/m ³ (150 ppm) STEL: 890 mg/m ³ (300 ppm) | PEL: 200 ppm | TWA: 450 mg/m ³ STEL: 900 mg/m ³ |

| CAS # | Hazardous components | Sweden OEL | Singapore | Britain EH40 |
|---------|----------------------|---|---|---|
| 78-93-3 | Methyl Ethyl Ketone | TWA: 150 mg/m ³ (50 ppm) STEL: 300 mg/m ³ (100 ppm) (15 min) | TWA: 590 mg/m ³ (200 ppm) STEL: 885 mg/m ³ (300 ppm) | TWA: 600 mg/m ³ (200 ppm) STEL: 899 mg/m ³ (300 ppm) |

| CAS # | Hazardous components | Switzerland OEL | Japan OEL | |
|---------|----------------------|-----------------|-----------|--|
| 78-93-3 | Methyl Ethyl Ketone | | | |

8.2 Exposure controls:

8.2.1 Appropriate engineering controls:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ventilation fans and other electrical service must be non-sparking and have an explosion-proof design.

8.2.2 Individual protection measures, such as personal protective equipment

Eye/Face protection: Wear chemical splash goggles.

Skin protection: Wear appropriate protective gloves to prevent skin exposure.

Respiratory protection: Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygienic Practices: DO NOT SMOKE IN WORK AREA! Promptly remove contaminated clothing. Wash immediately if skin becomes contaminated. Do not eat or drink in work area while using this product. Wash thoroughly at the end of the workday, before eating and using the restroom.

Safety Data Sheet

Date: 5/29/2020
 Product Number: 52-0032-01 Revision: B
 Product Name: Makeup, Alcohol Resistant

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | | |
|-----------------------------------|--|---|-------------------------|
| Appearance: | Colorless Liquid (Upon aging, clear or colorless fluids may develop a slight yellow tint which will not affect the product performance). | | |
| Odor: | Solvent | Odor threshold: | No data available |
| pH: | No data available | Melting point: | -87.00 C |
| Boiling range: | 80.00 C | Flash point: | -7°C |
| Evaporation rate: | 5.8 (BuAC=1) | Upper Explosive Limit: | - |
| | | Lower Explosive Limit: | - |
| Flammability: | No data available | Vapor Pressure: | 94.5 MM_HG at 20.0 C |
| Vapor density: | > Air | Relative Density: | 0.805 (H2O = 1 @ 20 °C) |
| Solubility(ies): | Miscible | Partition coefficient n-octanol/water: | No data available |
| Auto-ignition temperature: | 404.00 C | Decomposition temperature: | No data available |
| Viscosity: | No data available | | |
| Explosive properties: | > 99.0% Volatile by volume. | | |
| Oxidizing properties: | No data available | | |
| Percent Volatile: | 99.999 % by volume. | | |

9.2 Other information:

| | | | |
|---------------------|-------------------|-------------|-------------------|
| Miscibility: | No data available | VOC: | No data available |
|---------------------|-------------------|-------------|-------------------|

Section 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Will not occur

10.4 Conditions to avoid:

Ignition sources, Excess heat.

10.5 Incompatible materials:

Strong oxidizing agents, Strong acids, 2-propanol

Safety Data Sheet

Product Number: 52-0032-01 Date: 5/29/2020
 Product Name: Makeup, Alcohol Resistant Revision: B

10.6 Hazardous decomposition products

Carbon monoxide, Carbon dioxide.

Section 11: Toxicological information

11.1 Information on Toxicological effects

Acute toxicity: CAS# 78-93-3:
 Acute toxicity, LD50, Intraperitoneal, Mouse, 616.0 MG/KG.
 Result:
 Lungs, Thorax, or Respiration: Sputum.
 Biochemical: Metabolism (Intermediary): Other proteins.
 Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of inflammation.
 - Shell Chemical Company. Unpublished Report., Vol/p/yr: -,6, 1961

Acute toxicity, LD50, Skin, Species: Rabbit, 6480. MG/KG.
 Result:
 Lungs, Thorax, or Respiration:Other changes.
 Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of inflammation.
 - Shell Chemical Company., Vol/p/yr: MSDS-5390-,

Acute toxicity, LC50, Inhalation, Mouse, 32.00 MG/M3.
 Result:
 Brain and Coverings: Other degenerative changes.
 Biochemical:Metabolism (intermediary): Effect on inflammation or mediation of inflammation.

Acute toxicity, LD50, Intraperitoneal, Species: Guinea pig, 2.000 GM/KG.
 Result:
 Immunological Including Allergic: Increase in humoral immune response.

Skin No data available
corrosion/irritation:
Serious eye No data available
damage/irritation:
Respiratory or skin No data available
sensitization:
Germ cell Mutagenic effects have occurred in experimental animals.
mutagenicity:
Carcinogenicity: CAS# 78-93-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65.



Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

| | |
|--------------------------------|-------------------|
| Reproductive toxicity: | No data available |
| STOT-single exposure: | No data available |
| STOT-repeated exposure: | No data available |
| Aspiration hazard | No data available |

11.1.1 Hazard Class information:

No data available

11.1.2 Mixture toxicity:

No data available

11.1.3 Critical studies:

No data available

11.1.4 Non-compliance hazard class:

No data available

11.1.5 Information on likely routes of exposure:

No data available

11.1.6 Symptoms related to the physical, chemical and toxicological characteristics:

No data available

11.1.7 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

No data available

11.1.8 Interactive effects:

No data available

11.1.9 Absence of specific data:

No data available

11.1.10 Mixtures:

No data available

11.1.11 Mixture vs Substance information:

No data available

11.1.12 Other information:

No data available



Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

Section 12: Ecological information

12.1 Toxicity:

Environmental: Substance evaporates in water with T1/2= 3D (rivers) to 12D (lakes). Substance is not expected to bioconcentrate in marine life. Physical: Substance photodegrades in air with T1/2 = 2.3 days. Oxidizes rapidly by photo-chemical reactions in air. Readily biodegradable meeting the 10 day window criterion. Not expected to bioaccumulate significantly

12.2 Persistence and degradability:

No data available

12.3 Bioaccumulative potential:

No data available

12.4 Mobility in soil:

No data available

12.5 Results of PBT and vPvB assessment:

No data available

12.6 Other adverse effects:

No data available

Section 13: Disposal considerations

13.1 Waste treatment methods:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.
RCRA P-Series: None listed.
RCRA U-Series:
CAS# 78-93-3: waste number U159 (Ignitable waste, Toxic waste).

Section 14: Transport information

| | | |
|------|-----------------------|-------------------------------|
| 14.1 | UN number: | 1210 |
| 14.2 | Proper shipping name: | |
| | US DOT: | Printing Ink Related Material |

Safety Data Sheet

Date: 5/29/2020

Product Number: 52-0032-01

Revision: B

Product Name: Makeup, Alcohol Resistant

| | |
|---|--|
| Canadian TDG: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |
| European ADR/RID: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |
| IMDG/IMO: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |
| ICAO/IATA: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |
| 14.3 Transport hazard class(es) : | 3 - FLAMMABLE LIQUID |
| 14.4 Packing group: | II |
| 14.5 Environmental hazards: | N/A |
| 14.6 Special precautions for user: | N/A |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | N/A |

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

| EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists | | | | |
|---|----------------------|--------------|------------|--------------|
| CAS # | Hazardous components | S. 302 (EHS) | S. 304 RQ | S. 313 (TRI) |
| 78-93-3 | Methyl Ethyl Ketone | No | Yes 5000LB | No |

| CAS # | Hazardous components | Canadian NPRI | Canadian Toxic | Canadian DSL |
|---------|----------------------|---------------|----------------|--------------|
| 78-93-3 | Methyl Ethyl Ketone | Yes | No | Yes |

| CAS # | Hazardous components | CAA HAP, ODC | CWA NPDES | TSCA |
|---------|----------------------|--------------|-----------|-----------|
| 78-93-3 | Methyl Ethyl Ketone | No | No | Yes - Inv |

Safety Data Sheet

Product Number: 52-0032-01 Date: 5/29/2020
 Product Name: Makeup, Alcohol Resistant Revision: B

| CAS # | Hazardous components | CA Prop 65 | Mexico INSQ | Australia ICS |
|---------|----------------------|------------|-------------|---------------|
| 78-93-3 | Methyl Ethyl Ketone | No | Yes - 1193 | Listed |

| CAS # | Hazardous components | New Zealand IOC | China IECS | Japan ENCS |
|---------|----------------------|-----------------|------------|-------------|
| 78-93-3 | Methyl Ethyl Ketone | Listed | Listed | Yes - 2-542 |

| CAS # | Hazardous components | Japan ISHL | Korea ECL | Philippines |
|---------|----------------------|------------|--------------|-------------|
| 78-93-3 | Methyl Ethyl Ketone | Listed | Yes KE-24094 | Listed |

| CAS # | Hazardous components | Taiwan TCSCA | Singapore HSL | Israel HSL: |
|---------|----------------------|--------------|---------------|-------------|
| 78-93-3 | Methyl Ethyl Ketone | Listed | No | No |

| CAS # | Hazardous components | Germany WHCS | Switzerland Giftliste 1 | Switzerland INNS |
|---------|----------------------|--------------|-------------------------|------------------|
| 78-93-3 | Methyl Ethyl Ketone | Yes – 150 | Yes G-2429 | No |

| CAS # | Hazardous components | REACH | Kyoto GHG | Rotterdam |
|---------|----------------------|----------------|-----------|-----------|
| 78-93-3 | Methyl Ethyl Ketone | Yes - (R), (P) | No | No |

| CAS # | Hazardous components | Stockholm | | |
|---------|----------------------|-----------|--|--|
| 78-93-3 | Methyl Ethyl Ketone | No | | |

Canadian WHMIS Classification:



CLASS B, DIVISION 2: Flammable Liquids
 CLASS D, DIVISION 2, SUBDIVISION A: Very Toxic Materials (carcinogens, reproductive toxicity, etc.)



Safety Data Sheet

Date: 5/29/2020
Product Number: 52-0032-01 Revision: B
Product Name: Makeup, Alcohol Resistant

15.2 Chemical safety assessment

Section 16: Other information

Revision Date: 5/29/2020

Revision Notes: Format updated to (EU) 2015/830.

Additional Information:

Company Disclaimer:

The information and recommendations contained herein are, to the best of BestCode's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, BestCode recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not-permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, date and information furnished by BestCode hereunder are given gratis and BestCode assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.