

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2015/830

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name: Makeup, MEK/Acetone
Product Code: 52-0004-01

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product Use: Printing ink for use in BestCode CIJ

1.3 Details of the supplier of the safety data sheet

BestCode
3034 SE Loop 820
Fort Worth, TX 76140
817-349-8555

For further information, please contact Customer Service:

Customer Service: 817-349-8555
Email: Info@Bestcode.co

1.4 Emergency telephone number

Emergency Contact: Local Poison Information Center
Chem Tel. Inc. Toll Free 800-255-3924
International 813-248-0585

Section 2: Hazards identification

2.1 Classification of the mixture in accordance with Article 40 of Regulation (EC) No 1272/2008

GHS Rating:

Flammable Liquids, Category 2
Eye Damage/Irritation, Category 2A
Specific Target Organ Toxicity (single exposure), Category 3

2.2 Label elements



Signal word: Danger

Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

Hazard statements:

H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness

Precautionary statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P243 - Take precautionary measures against static discharge.

P242 - Use only non-sparking tools.

P264 - Wash hands thoroughly after handling.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P270- Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P285 - In case of inadequate ventilation wear respiratory protection

P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+378 - In case of fire, use carbon dioxide, dry chemical powder or appropriate foam to extinguish.

P403+235 - Store in cool/well-ventilated place.

P403+233 - Store container tightly closed in well-ventilated place.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local regulations.

2.3 Other Hazards

Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

Section 3: Composition/information on ingredients

3.1 Substances:

3.2 Mixtures:

CAS #	EC #	Hazardous components / REACH Registration No.	Concentration	GHS Classification
78-93-3	201-159-0	Methyl Ethyl Ketone	70.0 – 75%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; EUH066
67-64-1	200-662-2 606-001-00-8	Acetone	25.0-30.0%	Flam. Liq. 2: H225 Eye Damage 2: H319 STOT (SE) 3: H336 EUH066

Section 4: First Aid Measures

4.1 Description of first aid measures

Inhalation	Move person to fresh air, if they have problem breathing, show signs of overexposure or feel unwell obtain medical attention
Eyes:	Immediately flush eyes with cold water for several minutes while lifting upper and lower eyelids, Remove contact lenses if present and easy to do without injury to the eye and continue rinsing, If irritation persists seek medical aid
Skin:	Wash with soap and water, Remove any contaminated clothing and wash before reuse, If irritation occurs or persists seek medical aid
Ingestion:	DO NOT INDUCE VOMITING, rinse mouth with water, and drink small quantities of water, Call a physician, or poison control center, and get medical attention, If victim feels nauseous stop drinking, If vomiting occurs, keep head below hips to prevent aspiration into the lungs

4.2 Most Important symptoms and effects, both acute and delayed

Exposure may affect, central nervous system. Symptoms may include, narcotic effects

4.3 Indication of any immediate medical attention and special treatment needed

Notes to doctor: Contains Ketones, vomiting may cause aspiration pneumonia

Section 5: Fire Fighting Measures

5.1 Extinguishing media

SUITABLE: Use DRY chemicals, CO2 or alcohol foam, Water spray to cool or protect exposed materials,

UNSUITABLE: Avoid using a water stream. Product will float upon water and could spread any fire

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapor, May explode if ignited in an enclosed area, May form flammable or explosive vapor-air mixture, Flashback along vapor trail may occur, Containers may explode or erupt during a fire when heated excessively, Product will float and can be reignited on surface water

5.3 Advice for firefighters

Use MSHA/NIOSH approved self-contained breathing apparatus and full protective gear

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Follow all safety precautions, Wear Personal Protective Equipment, Do not walk through spill.

Safety Glasses, Chemical Gloves, Approved Respirator, Chemical Apron, Rubber Boots

6.1.1 For non-emergency personnel

Evacuate

6.1.2 For emergency responders

Warn personnel to move away and stay upwind from spill, Stop spill or release only if it can be done safely, Keep unprotected personnel from entering the hazard area, Eliminate ignition sources and ventilate area

6.2 Environmental Precautions

No data available.

6.3 Methods and material for containment and cleaning up

6.3.1 For Containment:

Use sand or inert non-combustible absorbent pads to prevent spill from spreading, Prevent spill from entering the environment, waterways, sewers, basements or confined areas

6.3.2 Clean up and disposal of spill:

Use sand or inert non-combustible absorbent pads or material. Collect product using non-sparking tools and place into approved container for proper disposal. Dispose of material in accordance with all State and Federal Guidelines and Regulations, Contact a licensed waste disposal contractor for proper disposal



Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

Section 7: Handling and storage

7.1 Precautions for safe handling

Keep away from incompatible materials, heat, sparks, electrical equipment, fire and all ignition sources, Do not get in eyes, on skin, or clothing, or breathe mist, vapor or fumes, Use appropriate safety equipment, and adequate ventilation, Do not smoke, eat or drink while using, Wash thoroughly after handling, Use only non-sparking tools, Avoid free fall of liquid, Ground containers when transferring, Empty containers are very hazardous, Do not flame cut, saw or drill. Refer to NFPA-704 and/or API RP 2003 for specific bonding and grounding requirements, Consulting with a Safety Equipment Supplier is recommended

7.2 Conditions for safe storage, including any compatibilities

Keep container closed when not in use, Store in a cool, well-ventilated area and away from incompatible materials, Store away from heat, sparks, open flames or hot surfaces, Store below 49°C (120°F) and in accordance with Class IB Flammable Liquids (GHS Category 2)

7.3 Specific end use(s)

Fluid delivery to BestCode Series 8 CIJ. Follow safety instructions outlined in 7.1 & 7.2 while handling. Observe warnings provided with BestCode Series 8 CIJ system when installing and handling fluids.

Section 8: Exposure control/personal protection

8.1 Control parameters

CAS #	Hazardous components	ACGIH TLV	Australia	Austria
78-93-3	Methyl Ethyl Ketone	TLV: 200 ppm STEL: 300 ppm	TWA: 295 mg/m3 (100 ppm) STEL: 590 mg/m3 (200 ppm)	TWA: 445 mg/m3 (150 ppm) STEL: 890 mg/m3 (300 ppm)
67-64-1	Acetone	TLV: 500 ppm STEL: 750 ppm	TWA: 1200 mg/m3 (500 ppm) STEL: 4800 mg/m3 (2000 ppm)	TWA: 1185 mg/m3 (500 ppm) STEL: 2375 mg/m3 (1000 ppm)

CAS #	Hazardous components	Belgium OEL	California, USA	Ontario, CA
78-93-3	Methyl Ethyl Ketone	TWA: 600 mg/m3 (200 ppm) STEL: 900 mg/m3 (300 ppm)	TWA: 590 mg/m3 (200 ppm) STEL: 885 mg/m3 (300 ppm)	TWA: 200 ppm STEL: 300 ppm
67-64-1	Acetone	TWA: 1210 mg/m3 (500 ppm) STEL: 2420 mg/m3 (1000 ppm)	TWA: 1200 mg/m3 (500 ppm) STEL: 1780 mg/m3 (750 ppm) CEIL: 3000 ppm	TWA: 500 ppm STEL: 750 ppm

Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

CAS #	Hazardous components	China	Québec, CA	German AGS
78-93-3	Methyl Ethyl Ketone	TWA: 300 mg/m ³ STEL: 600 mg/m ³ (15 min)	TWA: 150 mg/m ³ (50 ppm) STEL: 300 mg/m ³ (100 ppm)	TWA: 600 mg/m ³ (200 ppm) STEL: 600 mg/m ³ (200 ppm) (15 min)
67-64-1	Acetone			

CAS #	Hazardous components	Germany MAK/TRK	Denmark OEL	Spain OEL
78-93-3	Methyl Ethyl Ketone	TWA: 295 mg/m ³ (100 ppm) STEL: 600 mg/m ³ (200 ppm) (30min) (4x)	TWA: 145 mg/m ³ (50 ppm) STEL: 290 mg/m ³ (100 ppm)	TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm)
67-64-1	Acetone	TWA: 1200 mg/m ³ (500 ppm) STEL: 4800 m ³ /m ³ (15min) (4x) (2000 ppm (15min)(4x))	TWA: 600 mg/m ³ (250 ppm) STEL: 1200 mg/m ³ (500 ppm)	TWA: 1210 mg/m ³ (500 ppm)

CAS #	Hazardous components	Europe	Finland OEL	France VL
78-93-3	Methyl Ethyl Ketone	TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm)	STEL: 300 mg/m ³ (100 ppm) (15 min)	TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm)
67-64-1	Acetone	TWA: 1210 mg/m ³ (500 ppm)		TWA: 1210 mg/m ³ (500 ppm) STEL: 2420 mg/m ³ (1000 ppm)

CAS #	Hazardous components	Hungary OEL	Ireland OEL	Italy OEL
78-93-3	Methyl Ethyl Ketone	TWA: 600 mg/m ³ STEL: 900 mg/m ³	TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm) (15 min)	TWA: 600 mg/m ³ (200 ppm) STEL: 900 mg/m ³ (300 ppm)
67-64-1	Acetone	TWA: 1210 mg/m ³ STEL: 2420 mg/m ³	TWA: 1210 mg/m ³ (500 ppm)	TWA: 1210 mg/m ³ (500 ppm)

Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

CAS #	Hazardous components	South Korea	Latvia OEL	Mexico OEL
78-93-3	Methyl Ethyl Ketone	TWA: 590 mg/m ³ (200 ppm) STEL: 885 mg/m ³ (300 ppm)	TWA: 200 mg/m ³ (67 ppm) STEL: 900 mg/m ³ (300 ppm) (15 min)	TWA: 590 mg/m ³ (200 ppm) STEL: 885 mg/m ³ (300 ppm)
67-64-1	Acetone	TWA: 1188 mg/m ³ (500 ppm) STEL: 1782 mg/m ³ (750 ppm)	TWA: 1210 mg/m ³ (500 ppm)	TWA: 2400 mg/m ³ (1000 ppm) STEL: 3000 mg/m ³ (1260 ppm)

CAS #	Hazardous components	Malaysia OEL	NIOSH	Netherlands OEL
78-93-3	Methyl Ethyl Ketone	TWA: 590 mg/m ³ (200 ppm)	TWA: 200 ppm STEL: 300 ppm	TWA: 590 mg/m ³ STEL: 900 mg/m ³
67-64-1	Acetone	TWA: 1187 mg/m ³ (500 ppm)	TWA: 250 ppm	TWA: 1210 mg/m ³ STEL: 2420 mg/m ³

CAS #	Hazardous components	New Zealand	OSHA PELs	Poland
78-93-3	Methyl Ethyl Ketone	TWA: 445 mg/m ³ (150 ppm) STEL: 890 mg/m ³ (300 ppm)	PEL: 200 ppm	TWA: 450 mg/m ³ STEL: 900 mg/m ³
67-64-1	Acetone	TWA: 1185 mg/m ³ (500 ppm) STEL: 2375 mg/m ³ (1000 ppm)	PEL: 1000 ppm	TWA: 600 mg/m ³ STEL: 1800 mg/m ³

CAS #	Hazardous components	Sweden OEL	Singapore	Britain EH40
78-93-3	Methyl Ethyl Ketone	TWA: 150 mg/m ³ (50 ppm) STEL: 300 mg/m ³ (100 ppm) (15 min)	TWA: 590 mg/m ³ (200 ppm) STEL: 885 mg/m ³ (300 ppm)	TWA: 600 mg/m ³ (200 ppm) STEL: 899 mg/m ³ (300 ppm)
67-64-1	Acetone	TWA: 600 mg/m ³ (250 ppm) STEL: 1200 mg/m ³ (500 ppm) (15 min)	TWA: 1780 mg/m ³ (750 ppm) STEL: 2380 mg/m ³ (1000 ppm)	TWA: 1210 mg/m ³ (500 ppm) STEL: 3620 mg/m ³ (1500 ppm)



Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

CAS #	Hazardous components	Switzerland OEL	Japan OEL	
78-93-3	Methyl Ethyl Ketone			
67-64-1	Acetone	TWA: 1200 mg/m ³ (500 ppm) STEL: 2400 mg/m ³ (1000 ppm)	TWA: 750 ppm	

8.2 Exposure controls:

8.2.1 Appropriate engineering controls:

Ventilate to keep vapors of this material below the lowest ppm listed above, If over Threshold Limit Value use a MSHA / NIOSH approved respirator for organic vapor, supplied air or self-contained breathing apparatus

Access to a drench shower with eye wash station is a recommended safety precaution for handling / using this type of material.

8.2.2 Individual protection measures, such as personal protective equipment

Eye/Face protection: Wear safety glasses or goggles or face shield when handling / using this material

Skin protection: Wear chemical resistant impervious gloves when handling / using this material. Consult with supplier for recommendations regarding glove material / permeability / break through time. Wear chemical resistant impervious protective clothing if exposure is likely when handling / using this material. Wear chemical resistant impervious footwear if exposure is likely when handling / using this material

Respiratory protection: Wear a MSHA / NIOSH approved respirator at or above listed TLV's or if irritation is experienced.

Hygienic Practices: DO NOT SMOKE IN WORK AREA! Promptly remove contaminated clothing. Wash immediately if skin becomes contaminated. Do not eat or drink in work area while using this product. Wash thoroughly at the end of the workday, before eating and using the restroom.

Safety Data Sheet

Date: 3/26/2021
 Product Number: 52-0004-01 Revision: A
 Product Name: Makeup, MEK/Acetone

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Colorless Liquid (Upon aging, clear or colorless fluids may develop a slight yellow tint which will not affect the product performance).		
Odor:	Ketone	Odor threshold:	No data available
pH:	No data available	Melting point:	-95°C to -87°C
Boiling range:	56°C to 79°C	Flash point:	-7°C
Evaporation rate:	5.8 (BuAC=1)	Upper Explosive Limit:	11.5%
		Lower Explosive Limit:	1.8%
Flammability:	No data available	Vapor Pressure:	-
Vapor density:	> Air	Relative Density:	0.801 (H ₂ O = 1 @ 20 °C)
Solubility(ies):	27.0%	Partition coefficient n-octanol/water:	No data available
Auto-ignition temperature:	465°C	Decomposition temperature:	No data available
Viscosity:	~ 0.43 cP		
Explosive properties:	100.00% by volume.		
Oxidizing properties:	No data available		
Percent Volatile:	100.00% by volume.		

9.2 Other information:

Miscibility:	No data available	VOC:	75%
---------------------	-------------------	-------------	-----

Section 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under normal ambient and anticipated conditions of use

10.3 Possibility of hazardous reactions

Will not occur

10.4 Conditions to avoid:

Heat sources, sparks, flame or static discharge and incompatible materials

10.5 Incompatible materials:

Incompatible with, activated carbon, bases, phosphorous oxychloride, reducing agents, strong oxidizers

Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

10.6 Hazardous decomposition products

Burning or thermal decomposition can produce, carbon oxides

Section 11: Toxicological information

11.1 Information on Toxicological effects

Acute toxicity: **Oral:** 2,924 mg/kg **Dermal:** > 5,000 mg/kg **Inhaled:** > 20 mg/l

Acetone

LD50 Oral Rat 5,800 mg/kg (>2000 mg/kg)

LD50 Inhaled Rat 100.2 mg/l 4 Hours (Vapor) (>20 mg/l)

LD50 Dermal Guinea pig 7,426 mg/kg (>2000 mg/kg)

Methyl Ethyl Ketone

LD50 Oral Rat 2,193 mg/kg (>2000 mg/kg)

LD50 Inhaled Rat > 50 mg/l 4 Hours (Vapor) (>20 mg/l)

LD50 Dermal Rabbit 6,480 mg/kg (>2000 mg/kg)

Skin

corrosion/irritation:

Acute: May cause mild skin irritation

Chronic: Causes mild skin irritation, defatting of the skin which may lead to dermatitis

Serious eye

damage/irritation:

Acute: Can cause serious eye irritation

Chronic: Causes serious eye irritation

Respiratory or skin

sensitization:

Acute: May cause drowsiness or dizziness

Chronic: May cause drowsiness or dizziness, Symptoms may include, headache, dizziness or drowsiness, central nervous system depression

Ingestion:

Acute: May be harmful if swallowed, Ingestion may affect, liver, kidneys, central nervous system, Symptoms may include, headache, nausea, vomiting, abdominal pain, central nervous system depression.

Chronic: Can be harmful if swallowed, May cause lung damage if swallowed enters airways, Ingestion may affect, liver, kidneys, central nervous system, Symptoms may include, gastrointestinal irritation, inebriation, nausea, vomiting, abdominal pain, central nervous system depression

Mutagenic effects have occurred in experimental animals.

Germ cell

mutagenicity:

Carcinogenicity:

No data available

Reproductive toxicity:

No data available

STOT-single exposure:

No data available

STOT-repeated

No data available

exposure:

Aspiration hazard

No data available

Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

11.1.1 Hazard Class information:

No data available

11.1.2 Mixture toxicity:

No data available

11.1.3 Critical studies:

No data available

11.1.4 Non-compliance hazard class:

No data available

11.1.5 Information on likely routes of exposure:

Eyes, Skin, Ingestion, Inhalation.

Target Organs: Central Nervous System

11.1.6 Symptoms related to the physical, chemical and toxicological characteristics:

No data available

11.1.7 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

No data available

11.1.8 Interactive effects:

No data available

11.1.9 Absence of specific data:

No data available

11.1.10 Mixtures:

No data available

11.1.11 Mixture vs Substance information:

No data available

11.1.12 Other information:

Preexisting, central nervous system, disorders may be aggravated by exposure to this product



Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

Section 12: Ecological information

12.1 Toxicity:

Acetone

LC50 Mosquito Fish (*Gambusia affinis*) 13,000 mg/l 48 Hours 4 (>100 mg/l)

EC50 Water Flea (*Daphnia magna*) 8,800 mg/l 48 Hours 4 (>100 mg/l)

LC50 Rainbow Trout (*Oncorhynchus mykiss*) 5,540 mg/l 96 Hours 4 (>100 mg/l)

Methyl Ethyl Ketone

LD50 Fathead Minnow (*Pimephales promelas*) 2,993 mg/l 96 Hours 4 (>100 mg/l)

EC50 Green Algae (*Pseudokirchneriella* s.) 1,240 mg/l 72 Hours 4 (>100 mg/l)

EC50 Water Flea (*Daphnia magna*) 308 mg/l 48 Hours 4 (>100 mg/l)

12.2 Persistence and degradability:

This product is readily biodegradable according to the OECD definition

12.3 Bioaccumulative potential:

There is no evidence to suggest bioaccumulation will occur

12.4 Mobility in soil:

This material is a partially mobile liquid

12.5 Results of PBT and vPvB assessment:

No data available

12.6 Other adverse effects:

May be harmful to aquatic life

Section 13: Disposal considerations

13.1 Waste treatment methods:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.

Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series:

CAS# 67-64-1: waste number U002 (Ignitable waste).: waste number U154.

CAS# 78-93-3: waste number U159 (Ignitable waste, Toxic waste).

Safety Data Sheet

Product Number: 52-0004-01 Date: 3/26/2021
 Product Name: Makeup, MEK/Acetone Revision: A

Section 14: Transport information

14.1	UN number:	1210
14.2	Proper shipping name:	
	US DOT:	Printing Ink Related Material
	Canadian TDG:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	European ADR/RID:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	IMDG/IMO:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	ICAO/IATA:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
14.3	Transport hazard class(es) :	3 - FLAMMABLE LIQUID
14.4	Packing group:	II
14.5	Environmental hazards:	N/A
14.6	Special precautions for user:	N/A
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	N/A

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists				
CAS #	Hazardous components	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
78-93-3	Methyl Ethyl Ketone	No	Yes 5000LB	No
67-64-1	Acetone	No	Yes 5000LB	No

CAS #	Hazardous components	Canadian NPRI	Canadian Toxic	Canadian DSL
78-93-3	Methyl Ethyl Ketone	Yes	No	Yes
67-64-1	Acetone	No	No	Yes

Safety Data Sheet

Date: 3/26/2021

Product Number: 52-0004-01

Revision: A

Product Name: Makeup, MEK/Acetone

CAS #	Hazardous components	CAA HAP, ODC	CWA NPDES	TSCA
78-93-3	Methyl Ethyl Ketone	No	No	Yes - Inv
67-64-1	Acetone	No	No	Yes - Inv

CAS #	Hazardous components	CA Prop 65	Mexico INSQ	Australia ICS
78-93-3	Methyl Ethyl Ketone	No	Yes - 1193	Listed
67-64-1	Acetone	No	Listed	Listed

CAS #	Hazardous components	New Zealand IOC	China IECSC	Japan ENCS
78-93-3	Methyl Ethyl Ketone	Listed	Listed	Yes - 2-542
67-64-1	Acetone	Listed	Listed	Yes - 2-542

CAS #	Hazardous components	Japan ISHL	Korea ECL	Philippines
78-93-3	Methyl Ethyl Ketone	Listed	Yes KE-24094	Listed
67-64-1	Acetone	No	Yes KE-29367	Listed

CAS #	Hazardous components	Taiwan TCSCA	Singapore HSL	Israel HSL:
78-93-3	Methyl Ethyl Ketone	Listed	No	No
67-64-1	Acetone	Listed	No	No

CAS #	Hazardous components	Germany WHCS	Switzerland Giftliste 1	Switzerland INNS
78-93-3	Methyl Ethyl Ketone	Yes – 150	Yes G-2429	No
67-64-1	Acetone	Yes – 150	Yes G-2429	No

CAS #	Hazardous components	REACH	Kyoto GHG	Rotterdam
78-93-3	Methyl Ethyl Ketone	Yes - (R), (P)	No	No
67-64-1	Acetone	Yes - (R), (P)	No	No

CAS #	Hazardous components	Stockholm		
78-93-3	Methyl Ethyl Ketone	No		
67-64-1	Acetone	No		



Safety Data Sheet

Product Number: 52-0004-01 Date: 3/26/2021
Product Name: Makeup, MEK/Acetone Revision: A

15.2 Chemical safety assessment

Section 16: Other information

Revision Date: 3/26/2021

Revision Notes:

Additional Information:

Company Disclaimer:

The information and recommendations contained herein are, to the best of BestCode's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, BestCode recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not-permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by BestCode hereunder are given gratis and BestCode assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.