

# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2020/878

## **Section 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product Identifier**

Product Name: **Ink, MEK Black Pigment Cable**

Registration **Not Relevant (Mixture)**

Product Code: **51-0078-01**

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Product Use: Printing ink for use in BestCode CIJ

### **1.3 Details of the supplier of the safety data sheet**

BestCode

3034 SE Loop 820

Fort Worth, TX 76140

817-349-8555

**For further information, please contact Customer Service:**

Customer Service: 817-349-8555

Email: Info@Bestcode.co

### **1.4 Emergency telephone number**

Emergency Contact: Local Poison Information Center

Chem Tel. Inc. Toll Free 800-255-3924

International 813-248-0585

## **Section 2: Hazards identification**

### **2.1 Classification of the mixture in accordance with Article 40 of Regulation (EC) No 1272/2008**

**GHS Rating:**

Flammable Liquid 2 - H225

Serious Eye Damage/Eye Irritation 1 - H318

Specific Target Organ Toxicity (Single Exposure) 3 - H336

### **2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008 (CLP)





# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

**Signal word:** Danger

## Hazard statements:

H225 Highly flammable liquid and vapor.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

## Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing vapour/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/ doctor.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

## 2.3 Other Hazards

N/A

## Section 3: Composition/information on ingredients

### 3.1 Substances:

### 3.2 Mixtures:

Methyl Ethyl Ketone	CAS No: 78-93-3 EC No: 201-159-0 Index No: 606-002-00-3 REACH Reg. No: 01-2119457290-43-xxxx	80.0-90.0%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
---------------------	---	------------	--

# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

Propan-1-OL	CAS No: 71-23-8 EC No: 200-746-9	1.0-5.0%	Flam. Liq. 2: H225 Eye Damage 1: H319 STOT (SE) 3: H336

## Section 4: First Aid Measures

### 4.1 Description of first aid measures

**General Notes:** Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues

**Inhalation:** Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.

**Eyes:** Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

**Skin:** Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing

**Ingestion:** Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

### 4.2 Most Important symptoms and effects, both acute and delayed

**General Information:** If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

**Inhalation:** May cause drowsiness or dizziness.

**Ingestion:** May be harmful if swallowed.

**Skin Contact:** May cause irritation.

**Eye Contact:** Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to doctor:** No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!



# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

## **Section 5: Fire Fighting Measures**

### **5.1 Extinguishing media**

Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemicals, sand, dolomite etc. Do not use water, if avoidable

### **5.2 Special hazards arising from the substance or mixture**

The product is flammable. Heating may generate flammable vapours. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

### **5.3 Advice for firefighters**

Control run-off water by containing and keeping it out of sewers and watercourses. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## **Section 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

#### **6.1.1 For non-emergency personnel**

Evacuate

#### **6.1.2 For emergency responders**

Wear protective clothing as described in Section 8 of this safety data sheet.

### **6.2 Environmental Precautions**

Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible..

### **6.3 Methods and material for containment and cleaning up**

#### **6.3.1 For Containment:**

Keep combustible materials away from spillage.

#### **6.3.2 Clean up and disposal of spill:**

Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.



# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

## **Section 7: Handling and storage**

### **7.1 Precautions for safe handling**

Avoid spilling. Avoid contact with skin and eyes. Do not wear contact lenses. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Use explosion proof electric equipment. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.

### **7.2 Conditions for safe storage, including any compatibilities**

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

### **7.3 Specific end use(s)**

Fluid delivery to BestCode Series 8 CIJ. Follow safety instructions outlined in 7.1 & 7.2 while handling. Observe warnings provided with BestCode Series 8 CIJ system when installing and handling fluids

## **Section 8: Exposure control/personal protection**

### **8.1 Control parameters**

CAS #	Hazardous components	ACGIH TLV	Australia	Austria
78-93-3	Methyl Ethyl Ketone	TLV: 200 ppm STEL: 300 ppm	TWA: 295 mg/m3 (100 ppm) STEL: 590 mg/m3 (200 ppm)	TWA: 445 mg/m3 (150 ppm) STEL: 890 mg/m3 (300 ppm)
71-23-8	n-Propanol			

CAS #	Hazardous components	Belgium OEL	California, USA PELs	Ontario, CA
78-93-3	Methyl Ethyl Ketone	TWA: 600 mg/m3 (200 ppm) STEL: 900 mg/m3 (300 ppm)	TWA: 590 mg/m3 (200 ppm) STEL: 885 mg/m3 (300 ppm)	TWA: 200 ppm STEL: 300 ppm
71-23-8	n-Propanol			

CAS #	Hazardous components	China	Québec, CA	German AGS
78-93-3	Methyl Ethyl Ketone	TWA: 300 mg/m3 STEL: 600 mg/m3 (15 min)	TWA: 150 mg/m3 (50 ppm) STEL: 300 mg/m3 (100 ppm)	TWA: 600 mg/m3 (200 ppm) STEL: 600 mg/m3 (200 ppm) (15 min)

# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

71-23-8	n-Propanol			
---------	------------	--	--	--

CAS #	Hazardous components	Germany MAK/TRK	Denmark OEL	Spain OEL
78-93-3	Methyl Ethyl Ketone	TWA: 295 mg/m <sup>3</sup> (100 ppm) STEL: 600 mg/m <sup>3</sup> (200 ppm) (30min) (4x)	TWA: 145 mg/m <sup>3</sup> (50 ppm) STEL: 290 mg/m <sup>3</sup> (100 ppm)	TWA: 600 mg/m <sup>3</sup> (200 ppm) STEL: 900 mg/m <sup>3</sup> (300 ppm)
71-23-8	n-Propanol			

CAS #	Hazardous components	Europe	Finland OEL	France VL
78-93-3	Methyl Ethyl Ketone	TWA: 600 mg/m <sup>3</sup> (200 ppm) STEL: 900 mg/m <sup>3</sup> (300 ppm)	STEL: 300 mg/m <sup>3</sup> (100 ppm) (15 min)	TWA: 600 mg/m <sup>3</sup> (200 ppm) STEL: 900 mg/m <sup>3</sup> (300 ppm)
71-23-8	n-Propanol			

CAS #	Hazardous components	Hungary OEL	Ireland OEL	Italy OEL
78-93-3	Methyl Ethyl Ketone	TWA: 600 mg/m <sup>3</sup> STEL: 900 mg/m <sup>3</sup>	TWA: 600 mg/m <sup>3</sup> (200 ppm) STEL: 900 mg/m <sup>3</sup> (300 ppm) (15 min)	TWA: 600 mg/m <sup>3</sup> (200 ppm) STEL: 900 mg/m <sup>3</sup> (300 ppm)
71-23-8	n-Propanol			

CAS #	Hazardous components	South Korea	Latvia OEL	Mexico OEL
78-93-3	Methyl Ethyl Ketone	TWA: 590 mg/m <sup>3</sup> (200 ppm) STEL: 885 mg/m <sup>3</sup> (300 ppm)	TWA: 200 mg/m <sup>3</sup> (67 ppm) STEL: 900 mg/m <sup>3</sup> (300 ppm) (15 min)	TWA: 590 mg/m <sup>3</sup> (200 ppm) STEL: 885 mg/m <sup>3</sup> (300 ppm)
71-23-8	n-Propanol			

CAS #	Hazardous components	Malaysia OEL	NIOSH	Netherlands OEL
78-93-3	Methyl Ethyl Ketone	TWA: 590 mg/m <sup>3</sup> (200 ppm)	TWA: 200 ppm STEL: 300 ppm	TWA: 590 mg/m <sup>3</sup> STEL: 900 mg/m <sup>3</sup>
71-23-8	n-Propanol			

# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

CAS #	Hazardous components	New Zealand	OSHA PELs	Poland
78-93-3	Methyl Ethyl Ketone	TWA: 445 mg/m <sup>3</sup> (150 ppm) STEL: 890 mg/m <sup>3</sup> (300 ppm)	PEL: 200 ppm	TWA: 450 mg/m <sup>3</sup> STEL: 900 mg/m <sup>3</sup>
71-23-8	n-Propanol			

CAS #	Hazardous components	Sweden OEL	Singapore	Britain EH40
78-93-3	Methyl Ethyl Ketone	TWA: 150 mg/m <sup>3</sup> (50 ppm) STEL: 300 mg/m <sup>3</sup> (100 ppm) (15 min)	TWA: 590 mg/m <sup>3</sup> (200 ppm) STEL: 885 mg/m <sup>3</sup> (300 ppm)	TWA: 600 mg/m <sup>3</sup> (200 ppm) STEL: 899 mg/m <sup>3</sup> (300 ppm)
71-23-8	n-Propanol			

CAS #	Hazardous components	Switzerland OEL	Japan OEL	
78-93-3	Methyl Ethyl Ketone			
71-23-8	n-Propanol			

## 8.2 Exposure controls:

### 8.2.1 Appropriate engineering controls:

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Use engineering controls to reduce air contamination to permissible exposure level.

### 8.2.2 Individual protection measures, such as personal protective equipment

#### Eye/Face protection:

Contact lenses should not be worn when working with this chemical. The following protection should be worn: Chemical splash goggles.

#### Skin protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. For work of short duration or where a high degree of manual dexterity is needed, use protective gloves made of: Nitrile rubber. For work of long duration or where mechanical processes present a risk, use protective gloves made of: Butyl rubber. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

#### Respiratory protection:



# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

## Hygienic Practices:

Provide eyewash station. Wash promptly if skin becomes contaminated.  
Promptly remove non-impervious clothing that becomes contaminated.  
When using do not eat, drink or smoke.

## Section 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance:	Black Liquid		
Odor:	Solvent	Odor threshold:	-
pH:	-	Melting point:	-
Boiling range:	79°C	Flash point:	-9°C
Evaporation rate:	-	Upper Explosive Limit:	-
		Lower Explosive Limit:	-
Flammability:	-	Vapor Pressure:	-
Vapor density:	-	Relative Density:	-
Solubility(ies):	-	Partition coefficient n-octanol/water:	-
Auto-ignition temperature:	-	Decomposition temperature:	-
Viscosity:	-		
Explosive properties:	-		
Oxidizing properties:	-		

### 9.2 Other information:

VOC:	-
------	---

## Section 10: Stability and reactivity

### 10.1 Reactivity

Stable at normal ambient temperatures and when used as recommended.

### 10.2 Chemical stability

No particular stability concerns

### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

### 10.4 Conditions to avoid:

K Avoid heat, flames and other sources of ignition.

### 10.5 Incompatible materials:

No specific requirements are anticipated under normal conditions of use.



# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

## 10.6 Hazardous decomposition products

Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>.

## Section 11: Toxicological information

### 11.1 Information on Toxicological effects

**Acute toxicity:**

**Skin corrosion/irritation:**

**Serious eye damage/irritation:**

**Ingestion:**

**Inhalation:**

Repeated exposure may cause skin dryness or cracking.

Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain

Gastrointestinal symptoms, including upset stomach.

Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting

**Respiratory or skin sensitization:**

**Germ cell mutagenicity:**

**Carcinogenicity:**

**Reproductive toxicity:**

**STOT-single exposure:**

**STOT-repeated exposure:**

**Aspiration hazard**

#### 11.1.1 Hazard Class information:

#### 11.1.2 Mixture toxicity:

#### 11.1.3 Critical studies:

#### 11.1.4 Non-compliance hazard class:

#### 11.1.5 Information on likely routes of exposure:

#### 11.1.6 Symptoms related to the physical, chemical and toxicological characteristics:



# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

**11.1.7 Delayed and immediate effects as well as chronic effects from short and long-term exposure:**

**11.1.8 Interactive effects:**

**11.1.9 Absence of specific data:**

**11.1.10 Mixtures:**

**11.1.11 Mixture vs Substance information:**

**11.1.12 Other information:**

## **Section 12: Ecological information**

**12.1 Toxicity:** Harmful to aquatic life with long lasting effects.

**12.2 Persistence and degradability:** Not determined

**12.3 Bioaccumulative potential:** Not determined

**12.4 Mobility in soil:** The product is partly miscible with water and may spread in the aquatic environment

**12.5 Results of PBT and vPvB assessment:** Not determined

**12.6 Other adverse effects:** None known.

## **Section 13: Disposal considerations**

**13.1 Waste treatment methods:**

Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.



# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor. Containers should be thoroughly emptied before disposal because of the risk of an explosion.

## Section 14: Transport information

14.1	UN number:	1210
14.2	Proper shipping name:	
	US DOT:	Printing Ink
	Canadian TDG:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	European ADR/RID:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	IMDG/IMO:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
	ICAO/IATA:	Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable]
14.3	Transport hazard class(es) :	3 - FLAMMABLE LIQUID
14.4	Packing group:	II
14.5	Environmental hazards:	N/A
14.6	Special precautions for user:	N/A
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	
		N/A

## Section 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists				
CAS #	Hazardous components	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
78-93-3	Methyl Ethyl Ketone	No	Yes 5000LB	No

CAS #	Hazardous components	Canadian NPRI	Canadian Toxic	Canadian DSL
78-93-3	Methyl Ethyl Ketone	Yes	No	Yes



# Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

CAS #	Hazardous components	CAA HAP, ODC	CWA NPDES	TSCA
78-93-3	Methyl Ethyl Ketone	No	No	Yes - Inv

CAS #	Hazardous components	CA Prop 65	Mexico INSQ	Australia ICS
78-93-3	Methyl Ethyl Ketone	No	Yes - 1193	Listed

CAS #	Hazardous components	New Zealand IOC	China IECSC	Japan ENCS
78-93-3	Methyl Ethyl Ketone	Listed	Listed	Yes - 2-542

CAS #	Hazardous components	Japan ISHL	Korea ECL	Philippines
78-93-3	Methyl Ethyl Ketone	Listed	Yes KE-24094	Listed

CAS #	Hazardous components	Taiwan TCSCA	Singapore HSL	Israel HSL:
78-93-3	Methyl Ethyl Ketone	Listed	No	No

CAS #	Hazardous components	Germany WHCS	Switzerland Giftliste 1	Switzerland INNS
78-93-3	Methyl Ethyl Ketone	Yes – 150	Yes G-2429	No

CAS #	Hazardous components	REACH	Kyoto GHG	Rotterdam
78-93-3	Methyl Ethyl Ketone	Yes - (R), (P)	No	No

CAS #	Hazardous components	Stockholm		
78-93-3	Methyl Ethyl Ketone	No		

Canadian WHMIS Classification:

## 15.2 Chemical safety assessment

## Section 16: Other information



## Safety Data Sheet

Product Number: 51-0078-01

Product Name: Ink, MEK Black Pigment Cable

Date: 1/18/2023

Revision: A

**Revision Date:** 1/10/2022

**Revision Notes:** A: Updated Sections 1,2 and 3 for EU 2020/878

**Additional Information:**

### **Company Disclaimer:**

The information and recommendations contained herein are, to the best of BestCode's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, BestCode recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not-permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by BestCode hereunder are given gratis and BestCode assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.