

Safety Data Sheet

Product Number: 52-0001-01
Product Name: Makeup, MEK

Date: 2/16/2024
Revision: E

according to Regulation (EC) No. 1907/2006 as amended by (EC) No. 2020/878; US OSHA 29CFR 1910.1200
Revision E • Date of issue: 2-16-2024

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

Product Name: Makeup, MEK
Registration Number: Not Relevant (Mixture)
Product Code: 52-0001-01

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product Use: Printing ink for use in BestCode CIJ

1.3 Details of the supplier of the safety data sheet

BestCode
3034 SE Loop 820
Fort Worth, TX 76140
817-349-8555

For further information, please contact Customer Service:

Customer Service: 817-349-8555
Email: Info@Bestcode.co

1.4 Emergency telephone number

Emergency Contact: Local Poison Information Center
Chem Tel. Inc. Toll Free 800-255-3924
International 813-248-0585

Section 2: Hazards identification

2.1 Classification of the mixture in accordance with Article 40 of Regulation (EC) No 1272/2008 GHS Rating:

Flammable Liquids, Category 2
Serious Eye Damage/Eye Irritation, Category 2A
Specific Target Organ Toxicity (single exposure), Category 3

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)



Signal word: Danger



Safety Data Sheet

Date: 2/16/2024
Revision: E

Product Number: 52-0001-01
Product Name: Makeup, MEK

Hazard statements:

- H225 - Highly flammable liquid and vapor.
- H226 - Flammable liquid and vapor.
- H319 - Causes serious eye irritation.
- H336 - May cause drowsiness or dizziness.

Precautionary statements:

- P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 - Keep container tightly closed.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 - Wash hands thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
- P337+313 - If eye irritation persists, get medical advice/attention.
- P405 - Store locked up.
- P501 Dispose of contents/container to industrial combustion plant.

Supplemental Hazard Information

Hazardous Ingredients for Labelling

Methyl Ethyl Ketone

2.3 Other Hazards

Section 3: Composition/information on ingredients

3.1 Substances:

Not relevant (Mixture)

Safety Data Sheet

Date: 2/16/2024
Revision: E

Product Number: 52-0001-01
Product Name: Makeup, MEK

3.2 Mixtures:

| Name of Substance | Identifier | Concentration | GHS Classification |
|---------------------|---|---------------|--|
| Methyl Ethyl Ketone | CAS No: 78-93-3 EC No: 201-159-0 Index No: 606-002-00-3 REACH Reg. No: 01-2119457290-43-xxxx | 90.0-100% | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; |
| Ethanol | CAS No: 64-17-5 EC No: 200-578-6 Index No: 603-002-00-5 REACH Reg. No: 01-2119457610-43-xxxx | 0.0-10.0% | Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 |

Section 4: First Aid Measures

4.1 Description of first aid measures

Inhalation If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Eyes: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin: Wash off with soap and plenty of water. Consult a physician.

Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
Rinse mouth with water. Consult a physician.

4.2 Most Important symptoms and effects, both acute and delayed

Inhalation No Data Available
Eye contact No Data Available
Skin contact No Data Available
Ingestion No Data Available

4.3 Indication of any immediate medical attention and special treatment needed

Notes to doctor: No data available.

Section 5: Fire Fighting Measures

5.1 Extinguishing media

Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam..

5.2 Special hazards arising from the substance or mixture

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

5.3 Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Use proper personal protective equipment as indicated in Section 8.

6.1.2 For emergency responders

Use proper personal protective equipment as indicated in Section 8.

6.2 Environmental Precautions

Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

6.3.1 For Containment:

6.3.2 Clean up and disposal of spill:

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).



Safety Data Sheet

Product Number: 52-0001-01
 Product Name: Makeup, MEK

Date: 2/16/2024
 Revision: E

Section 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

7.2 Conditions for safe storage, including any compatibilities

Store under inert gas. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Hygroscopic.
 Storage class 510) Handle and store under inert gas.
 Recommended storage temperature: 2 -8 - 8 deg.C.

7.3 Specific end use(s)

Fluid delivery to BestCode Series 8 CIJ. Follow safety instructions outlined in 7.1 & 7.2 while handling. Observe warnings provided with BestCode Series 8 CIJ system when installing and handling fluids.

Section 8: Exposure control/personal protection

8.1 Control parameters

| CAS # | Chemical Name | Australia | Austria | Belgium |
|---------|---------------------|--|--|---|
| 64-17-5 | Ethanol | TWA: 1000ppm (1880mg/m3) | TWA: 1000ppm (1900mg/m3) STEL: 2000ppm (3800mg/m3) | TWA: 1000ppm (1907mg/m3) |
| 78-93-3 | Methyl Ethyl Ketone | TWA 150ppm (445mg/m3) STEL 300ppm (890mg/m3) | TWA 100ppm (295mg/m3) STEL 200ppm (590mg/m3) | TWA 200ppm (600mg/m3) STEL 300ppm (900mg/m3) |

| CAS # | Chemical Name | Ontario, CA | Québec, CA | Denmark |
|---------|---------------------|---------------------------|--|---|
| 64-17-5 | Ethanol | STEL: 1000ppm | TWA: 1000ppm (1880mg/m3) | TWA: 1000ppm (1900mg/m3) STEL: 2000ppm (3800mg/m3) |
| 78-93-3 | Methyl Ethyl Ketone | TWA 200ppm STEL 300ppm | TWA 50ppm (150mg/m3) STEL 100ppm (300mg/m3) | TWA 50ppm (145mg/m3) STEL 100ppm (290mg/m3) |

Safety Data Sheet

Product Number: 52-0001-01
Product Name: Makeup, MEK

Date: 2/16/2024
Revision: E

| CAS # | Chemical Name | European Union | Finland | France |
|---------|---------------------|---|---|---|
| 64-17-5 | Ethanol | - | TWA: 1000ppm (1900mg/m3) STEL: 1300ppm (2500mg/m3) | TWA: 1000ppm (1900mg/m3) STEL: 5000ppm (9500mg/m3) |
| 78-93-3 | Methyl Ethyl Ketone | TWA 200ppm (600mg/m3) STEL 300ppm (900mg/m3) | TWA 20ppm (60mg/m3) STEL 100ppm (300mg/m3) | TWA 200ppm (600mg/m3) STEL 300ppm (900mg/m3) |

| CAS # | Chemical Name | German AGS | Germany DFG | Hungary |
|---------|---------------------|--|--|-----------------------------------|
| 64-17-5 | Ethanol | TWA: 200ppm (380mg/m3) STEL: 800ppm (1520mg/m3) | TWA: 200ppm (380mg/m3) STEL: 800ppm (1520mg/m3) | TWA 1900mg/m3 |
| 78-93-3 | Methyl Ethyl Ketone | TWA 200ppm (600mg/m3) STEL 200ppm (600mg/m3) | TWA 200ppm (600mg/m3) STEL 200ppm (600mg/m3) | TWA (600mg/m3) STEL (900mg/m3) |

| CAS # | Chemical Name | Ireland | Italy | Latvia |
|---------|---------------------|---|---|--|
| 64-17-5 | Ethanol | STEL: 1000ppm | - | TWA 1000mg/m3 |
| 78-93-3 | Methyl Ethyl Ketone | TWA 200ppm (600mg/m3) STEL 200ppm (600mg/m3) | TWA 200ppm (600mg/m3) STEL 200ppm (600mg/m3) | TWA 67ppm (200mg/m3) STEL 300ppm (900mg/m3) |

| CAS # | Chemical Name | New Zealand | PROC | Poland |
|---------|---------------------|---|---|--------------------------------------|
| 64-17-5 | Ethanol | TWA: 1000ppm (1880mg/m3) | | TWA: (1900mg/m3) |
| 78-93-3 | Methyl Ethyl Ketone | TWA 150ppm (445mg/m3) STEL 300ppm (890mg/m3) | TWA (300mg/m3) STEL (600mg/m3) | TWA (450mg/m3) STEL (900mg/m3) |



Safety Data Sheet

Product Number: 52-0001-01
 Product Name: Makeup, MEK

Date: 2/16/2024
 Revision: E

| CAS # | Chemical Name | Romania | Singapore | South Korea |
|---------|---------------------|---|--|--|
| 64-17-5 | Ethanol | TWA: 1000ppm (1900mg/m ³) STEL: 5000ppm (9500mg/m ³) | TWA: 1000ppm (1880mg/m ³) | TWA: 1000ppm (1900mg/m ³) |
| 78-93-3 | Methyl Ethyl Ketone | TWA 200ppm (600mg/m ³) STEL 300ppm (900mg/m ³) | TWA 200ppm (590mg/m ³) STEL 300ppm (885mg/m ³) | TWA 200ppm (590mg/m ³) STEL 300ppm (885mg/m ³) |

| CAS # | Chemical Name | Spain | Sweden | Switzerland |
|---------|---------------------|---|--|---|
| 64-17-5 | Ethanol | STEL: 1000ppm (1910mg/m ³) | TWA: 500ppm (1000mg/m ³) STEL: 1000ppm (1900mg/m ³) | TWA: 500ppm (960mg/m ³) STEL: 1000ppm (1920mg/m ³) |
| 78-93-3 | Methyl Ethyl Ketone | TWA 200ppm (600mg/m ³) STEL 200ppm (600mg/m ³) | TWA 500ppm (150mg/m ³) STEL 300ppm (900mg/m ³) | TWA 200ppm (590mg/m ³) STEL 200ppm (590mg/m ³) |

| CAS # | Chemical Name | The Netherlands | USA - NIOSH | United Kingdom |
|---------|---------------------|--|--|---|
| 64-17-5 | Ethanol | TWA: (260mg/m ³) STEL: (1900mg/m ³) | TWA: 1000ppm (1900mg/m ³) | TWA: 1000ppm (1920mg/m ³) |
| 78-93-3 | Methyl Ethyl Ketone | TWA (590mg/m ³) STEL (900mg/m ³) | TWA 200ppm (500mg/m ³) STEL 300ppm (885mg/m ³) | TWA 200ppm (600mg/m ³) STEL 300ppm (899mg/m ³) |

| CAS # | Chemical Name | OSHA PELs | ACGIH TLV | California, USA PELs |
|---------|---------------------|--------------------------------------|---------------------------|---|
| 64-17-5 | Ethanol | TWA 1000ppm (1900mg/m ³) | STEL: 1000 ppm | PEL 1000ppm (1900mg/m ³) |
| 78-93-3 | Methyl Ethyl Ketone | TWA 200ppm (590mg/m ³) | TWA 200ppm STEL 300ppm | TWA 200ppm (500mg/m ³) STEL 300ppm (885mg/m ³) |

| CAS # | Chemical Name | Mexico |
|---------|---------------------|----------------------|
| 64-17-5 | Ethanol | CT 1000ppm |
| 78-93-3 | Methyl Ethyl Ketone | PPT 200ppm CT 300ppm |



Safety Data Sheet

Date: 2/16/2024
Revision: E

Product Number: 52-0001-01
Product Name: Makeup, MEK

8.2 Exposure controls:

8.2.1 Appropriate engineering controls:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

8.2.2 Individual protection measures, such as personal protective equipment

Wear appropriate protective clothing to prevent skin exposure. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Eye/Face protection: Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Ingredient CAS# 78-93-3, Methyl ethyl ketone:
Wear appropriate protective gloves to prevent skin exposure.

Respiratory protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact:

Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 292 min.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Full contact.

Material: Nitrile rubber, Minimum layer thickness: 0.4 mm, Break through time: 480 min.

Hygienic Practices: DO NOT SMOKE IN WORK AREA! Promptly remove contaminated clothing. Wash immediately if skin becomes contaminated. Do not eat or drink in work area while using this product. Wash thoroughly at the end of the workday, before eating and using the restroom.

Safety Data Sheet

Product Number: 52-0001-01
Product Name: Makeup, MEK

Date: 2/16/2024
Revision: E

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | | |
|-----------------------------------|--|---|---------------------------|
| Appearance: | Clear Liquid (Upon aging, clear or colorless fluids may develop a slight yellow tint which will not affect the product performance). | | |
| Odor: | Solvent | Odor threshold: | No data available |
| pH: | No data available | Melting point: | -89.50 C - 129.10 C |
| Boiling range: | 80.00-82.00 C | Flash point: | -2.99°C |
| Evaporation rate: | - | Upper Explosive Limit: | - |
| | | Lower Explosive Limit: | - |
| Flammability: | No data available | Vapor Pressure: | ~ 82-94.5 MM_HG at 20.0 C |
| Vapor density: | > Air | Relative Density: | .8005 |
| Solubility(ies): | Miscible | Partition coefficient n-octanol/water: | No data available |
| Auto-ignition temperature: | - | Decomposition temperature: | No data available |
| Viscosity: | No data available | | |
| Explosive properties: | No data available | | |
| Oxidizing properties: | No data available | | |

9.2 Other information:

| | | | |
|---------------------|-------------------|-------------|-------------------|
| Miscibility: | No data available | VOC: | No data available |
|---------------------|-------------------|-------------|-------------------|

Section 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Will not occur

10.4 Conditions to avoid:

Ignition sources, Excess heat, confined spaces, Incompatible materials, oxidizers.

10.5 Incompatible materials:

Safety Data Sheet

Product Number: 52-0001-01
Product Name: Makeup, MEK

Date: 2/16/2024
Revision: E

Strong oxidizing agents, Strong acids, 2-propanol, acids, Alkali metals, Ammonia, hydrazine, Peroxides, Sodium, Acid anhydrides, calcium hypochlorite, chromyl chloride, nitrosyl perchlorate, bromine pentafluoride, Perchloric acid, silver nitrate, mercuric nitrate, potassium tert-butoxide, magnesium perchlorate, Acid chlorides, platinum, uranium hexafluoride, silver oxide, iodine heptafluoride, acetyl bromide, disulfuryl difluoride, tetrachlorosilane + water, acetyl chloride, permanganic acid, ruthenium (VIII) oxide, uranyl perchlorate, potassium dioxide.

10.6 Hazardous decomposition products

Carbon monoxide, Carbon dioxide, Peroxides, irritating and toxic fumes and gases.

Section 11: Toxicological information

11.1 Information on Toxicological effects

Acute toxicity:

CAS# 78-93-3:

Acute toxicity, LD50, Intraperitoneal, Mouse, 616.0 MG/KG.

Result:

Lungs, Thorax, or Respiration: Sputum.

Biochemical: Metabolism (Intermediary): Other proteins.

Biochemical: Metabolism (intermediary): Effect on inflammation or mediation of inflammation.

- Shell Chemical Company. Unpublished Report., Vol/p/yr: -,6, 1961
Acute toxicity, LD50, Skin, Species: Rabbit, 6480. MG/KG.

Result:

Lungs, Thorax, or Respiration: Other changes.

Biochemical: Metabolism (intermediary): Effect on inflammation or mediation of inflammation.

- Shell Chemical Company., Vol/p/yr: MSDS-5390-,
Acute toxicity, LC50, Inhalation, Mouse, 32.00 MG/M3.

Result:

Brain and Coverings: Other degenerative changes.

Biochemical: Metabolism (intermediary): Effect on inflammation or mediation of inflammation.

Acute toxicity, LD50, Intraperitoneal, Species: Guinea pig, 2.000
GM/KG.

Safety Data Sheet

Date: 2/16/2024
Revision: E

Product Number: 52-0001-01
Product Name: Makeup, MEK

| | |
|------------------------------|---|
| | Result: |
| | Immunological Including Allergic: Increase in humoral immune response. |
| Skin | No data available |
| corrosion/irritation: | |
| Serious eye | No data available |
| damage/irritation: | |
| Respiratory or skin | No data available |
| sensitization: | |
| Germ cell | Mutagenic effects have occurred in experimental animals. |
| mutagenicity: | |
| Carcinogenicity: | Ingredient CAS# 78-93-3, Methyl ethyl ketone: CAS# 78-93-3: Not listed by ACGIH, IARC, NTP, or CA Prop 65. |
| | Ingredient CAS# 64-17-5, Ethyl alcohol: CAS# 64-17-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65. |
| Reproductive | No data available |
| toxicity: | |
| STOT-single | No data available |
| exposure: | |
| STOT-repeated | No data available |
| exposure: | |
| Aspiration hazard | No data available |

11.1.1 Hazard Class information:

No data available

11.1.2 Mixture toxicity:

No data available

11.1.3 Critical studies:

No data available

11.1.4 Non-compliance hazard class:

No data available

11.1.5 Information on likely routes of exposure:

No data available

11.1.6 Symptoms related to the physical, chemical and toxicological characteristics:

No data available

11.1.7 Delayed and immediate effects as well as chronic effects from short and long-term exposure:

No data available

11.1.8 Interactive effects:

No data available

11.1.9 Absence of specific data:

No data available

11.1.10 Mixtures:

No data available

11.1.11 Mixture vs Substance information:

No data available

11.1.12 Other information:

No data available

Section 12: Ecological information

12.1 Toxicity:

Ingredient CAS# 78-93-3, Methyl ethyl ketone:

Environmental: Substance evaporates in water with T1/2= 3D (rivers) to 12D (lakes). Substance is not expected to bioconcentrate in marine life. Physical: Substance photodegrades in air with T1/2 = 2.3 days. Oxidizes rapidly by photo-chemical reactions in air. Readily biodegradable meeting the 10 day window criterion. Not expected to bioaccumulate significantly.

Other: No information available.

Ingredient CAS# 64-17-5, Ethyl alcohol:

When released to the atmosphere it will photodegrade in hours (polluted urban atmosphere) to an estimated range of 4 to 6 days in less polluted areas. Rainout should be significant.

Physical: No information available.

12.2 Persistence and degradability:

No data available

12.3 Bioaccumulative potential:

No data available



Safety Data Sheet

Date: 2/16/2024
Revision: E

Product Number: 52-0001-01
Product Name: Makeup, MEK

12.4 Mobility in soil:

No data available

12.5 Results of PBT and vPvB assessment:

No data available

12.6 Other adverse effects:

No data available

Section 13: Disposal considerations

13.1 Waste treatment methods:

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Section 14: Transport information

| | | |
|-------------|------------------------------|--|
| 14.1 | UN number: | 1210 |
| 14.2 | Proper shipping name: | |
| | US DOT: | Printing Ink Related Material |
| | Canadian TDG: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |
| | European ADR/RID: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |
| | IMDG/IMO: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |



Safety Data Sheet

Date: 2/16/2024
Revision: E

Product Number: 52-0001-01
Product Name: Makeup, MEK

| | | |
|-------------|--|--|
| | ICAO/IATA: | Printing ink, [flammable or] Printing ink related material [(including printing ink thinning or reducing compound), flammable] |
| 14.3 | Transport hazard class(es) : | 3 - FLAMMABLE LIQUID |
| 14.4 | Packing group: | II |
| 14.5 | Environmental hazards: | N/A |
| 14.6 | Special precautions for user: | N/A |
| 14.7 | Transport in bulk according to Annex II of Marpol and the IBC Code: | N/A |

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

| EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists | | | | |
|---|----------------------|--------------|-----------|--------------|
| CAS # | Hazardous components | S. 302 (EHS) | S. 304 RQ | S. 313 (TRI) |
| 64-17-5 | Ethanol | - | - | - |
| 78-93-3 | Methyl Ethyl Ketone | - | - | - |

| CAS # | Hazardous components | Canadian NPRI | Canadian Toxic | Canadian DSL |
|---------|----------------------|---------------|----------------|--------------|
| 64-17-5 | Ethanol | Active | - | - |
| 78-93-3 | Methyl Ethyl Ketone | Active | - | 5000lbs |

Section 16: Other information

Revision Date: 2-16-2024

Revision Notes: B: Format updated to (EU) 2015/830. New concentration ranges in Section 3. Updated Section 9 tables to reflect new concentration ranges.
C: Updated Sections 8 and 15.
D: Updated for (EU) 2020/878
E: Added US Osha 29CFR 1910.1200

Additional Information:

Company Disclaimer:

The information and recommendations contained herein are, to the best of BestCode's knowledge and belief, accurate and reliable as of the date issued. Because many factors may affect processing or application/use, BestCode recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures



Safety Data Sheet

Product Number: 52-0001-01
Product Name: Makeup, MEK

Date: 2/16/2024
Revision: E

should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by BestCode hereunder are given gratis and BestCode assumes no obligation or liability for the description, designs, data and information given or results obtained. All such being given and accepted at your risk.